











































PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	Diameter of Fog
	PC-2801F, 3WA-860A	fog machine, mist system	0.2L/min, plastic cover, axial pump (2 plungers)	24V	60W	40Bar, 580PSI	4-10°C	0.2L/min	35m ²	< 7μm
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger		
< 7μm	24 hours	27*16*17, 4kgs	CE	min 100PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package    									
10m nylon hose, 6 nozzles and 7 slip lock	DLQ-6062									







PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	Diameter of Fog	
	PC-2801D, 3WA-860	fog machine, mist system	0.3L/min, plastic cover, with digital timer, axial pump (2 plungers)	24V	120W	60Bar, 860PSI	4-10℃	0.3L/min	75m ²	< 7μm	
	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automaticaly when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer				
	12 hours	45*25*28, 10kgs	CE	min 50PCS	15 days after payment	1 cartons/unit					
Accessories	<div style="display: flex; justify-content: space-around; align-items: center;">      </div> <p style="text-align: center;">DLQ-6062</p>										
15m nylon hose, 10 nozzles and 11 slip lock connectors (20m nylon hose, 18 nozzles and 19 slip lock connectors)	<div style="display: flex; justify-content: space-around; align-items: center;">     </div>										






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	Diameter of Fog
	PC-2801E, 3WA-860	fog machine, mist system	0.3L/min, SS cover, with digital timer, axial pump (2 plungers)	24V	120W	60Bar, 860PSI	4-10°C	0.3L/min	75m²	< 7µm
	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1) Stop working automatically when lack of water 2) Fog can spray with different frequencies 3) controlled by the Timer			
12 hours	38*18*45, 12kgs	CE	min 50PCS	15 days after payment	1 cartons/unit					
Accessories	Pictures of the Accessories and the Package	   								
15m nylon hose, 10 nozzles and 11 slip lock connectors (20m nylon hose, 18 nozzles and 19 slip lock connectors)										






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2801, 3WA-860A	fog machine, mist system	0.3L/min, iron cover, with digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	120W	60Bar, 860PSI	4-10°C	0.3L/min	50m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automatically when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer		
< 7μm	12 hours	45*23*28, 10kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	  					 			
5m nylon hose, 1 brass ring tube(5 nozzle seats), 5 nozzles		DLQ-6101	DLQ-6062							






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2801A, 3WA-860A	fog machine, mist system	0.3L/min, iron cover, no digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	120W	60Bar, 860PSI	4-10°C	0.3L/min	50m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger		
< 7µm	12 hours	45*23*28, 10kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories 5m nylon hose, 1 brass ring tube(5 nozzle seats), 5 nozzles	Pictures of the Accessories and the Package	 DLQ-6101		 DLQ-6062						






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2801B, 3WA-860A	fog machine, mist system	0.3L/min, SS cover, with digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	120W	60Bar, 860PSI	4-10°C	0.3L/min	50m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1) Stop working automatically when lack of water 2) Fog can spray with different frequencies 3) Controlled by the Timer		
< 7μm	12 hours	45*23*28, 10kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	  								
5m nylon hose, 1 brass ring tube(5 nozzle seats), 5 nozzles		DLQ-6101	DLQ-6062							






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2801C, 3WA-860A	fog machine, mist system	0.3L/min, SS cover, no digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	120W	60Bar, 860PSI	4-10°C	0.3L/min	50m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger			
< 7µm	12 hours	45*23*28, 10kgs	CE	min 50PCS	15 days after payment	1 cartons/unit					
Accessories	Pictures of the Accessories and the Package	  					 				
5m nylon hose, 1 brass ring tube(5 nozzle seats), 5 nozzles		DLQ-6101		DLQ-6062							






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2802, 3WA-860	fog machine, mist system	1L/min, iron cover, with digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	300W	60Bar, 860PSI	4-10℃	1L/min	100m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automaticaly when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer		
Accessories	<div style="display: flex; justify-content: space-around; align-items: center;"> <div data-bbox="517 1062 674 1192"> Pictures of the Accessories and the Package </div> <div data-bbox="674 962 1025 1192">  </div> <div data-bbox="1025 962 1267 1192">  <p>DLQ-6062</p> </div> <div data-bbox="1267 962 1675 1192">  </div> <div data-bbox="1675 962 2049 1192">  </div> </div>									
25m nylon hose, 20 nozzles and 21 slip lock connectors										






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2802A, 3WA-860	fog machine, mist system	1L/min, iron cover, no digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	300W	60Bar, 860PSI	4-10℃	1L/min	100m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger			
	< 7μm	12 hours	47*26*30, 12.5kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	   									
25m nylon hose, 20 nozzles and 21 slip lock connectors		DLQ-6062									






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2802B, 3WA-860	fog machine, mist system	1L/min, SS cover, with digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	300W	60Bar, 860PSI	4-10°C	1L/min	100m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automatically when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer			
< 7µm	12 hours	47*26*30, 12.5kgs	CE	min 50PCS	15 days after payment	1 cartons/unit					
Accessories	Pictures of the Accessories and the Package	   									
25m nylon hose, 20 nozzles and 21 slip lock connectors		DLQ-6062									






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2802C, 3WA-860	fog machine, mist system	1L/min, SS cover, no digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	300W	60Bar, 860PSI	4-10°C	1L/min	100m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger		
< 7μm	12 hours	47*26*30, 12.5kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	   								
25m nylon hose, 20 nozzles and 21 slip lock connectors		DLQ-6062								






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2803, 3WA-860	fog machine, mist system	3L/min, SS cover, with digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	750W	60Bar, 860PSI	4-10°C	3L/min	300m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automatically when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer			
< 7µm	12 hours	53*28*32, 20kgs	CE	min 50PCS	15 days after payment	1 cartons/unit					
Accessories	Pictures of the Accessories and the Package	   									
50m nylon hose, 45 nozzles and 46 slip lock connectors		DLQ-6062									






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2803A, 3WA-860	fog machine, mist system	3L/min, SS cover, no digital timer, axial pump (2 plungers)	220V/110V	50Hz/60Hz	750W	60Bar, 860PSI	4-10°C	3L/min	300m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger			
Accessories	Pictures of the Accessories and the Package					 DLQ-6062					
50m nylon hose, 45 nozzles and 46 slip lock connectors											

PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2803B, 3WZ-1208	fog machine, mist system	3L/min, SS cover, with digital timer, crank pump (3 plungers)	220V/110V	50Hz/60Hz	750W	60Bar, 860PSI	4-10°C	3L/min	300m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automaticaly when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer		
< 7µm	12 hours	55*25*30, 24kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories 50m nylon hose, 45 nozzles and 46 slip lock connectors	Pictures of the Accessories and the Package	    <p style="text-align: center;">DLQ-6062</p>								






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2802D, 3WZ-1206	fog machine, mist system	2L/min, SS cover, with digital timer, crank pump (3 plungers)	220V/110V	50Hz/60Hz	550W	60Bar, 860PSI	4-10°C	2L/min	200m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1) Stop working automatically when lack of water 2) Fog can spray with different frequencies controlled by the Timer			
	< 7µm	12 hours	55*25*30, 24kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	   									
30m nylon hose, 30 nozzles and 31 slip lock connectors		DLQ-6062									






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2804, 3WZ-1510	fog machine, mist system	7L/min, SS cover, with digital timer, crank pump (3 plungers)	220V/110V	50Hz/60Hz	1.8KW	60Bar, 860PSI	4-10°C	7L/min	600m²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automaticaly when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer			
	< 7µm	12 hours	69*35*33, 33kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	   									
100m nylon hose, 90 nozzles and 91 slip lock connectors											






PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY									
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area
	PC-2804A, 3WZ-1510	fog machine, mist system	7L/min, SS cover, no digital timer, crank pump (3 plungers)	220V/110V	50Hz/60Hz	1.8KW	60Bar, 860PSI	4-10°C	7L/min	600m ²
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger		
< 7μm	12 hours	69*35*33, 33kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories 100m nylon hose, 90 nozzles and 91 slip lock connectors	Pictures of the Accessories and the Package	    <p style="text-align: center;">DLQ-6062</p>								

PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2805, 3WZ-1810	fog machine, mist system	11L/min, SS cover, with digital timer, crank pump (3 plungers)	220V	50Hz/60Hz	2.2KW	60Bar, 860PSI	4-10°C	11L/min	800m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1) Stop working automatically when lack of water 2) Fog can spray with different frequencies 3) controlled by the Timer			
	< 7µm	12 hours	72*40*40, 50kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package    										
160m nylon hose, 160 nozzles and 161 slip lock connectors											

DLQ-6062

PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2805A, 3WZ-1814	fog machine, mist system	15.4L/min, SS cover, with digital timer, crank pump (3 plungers)	220V/380V	50Hz/60Hz	3KW	60Bar, 860PSI	4-10°C	15.4L/min	1000m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Advantage: 1)Stop working automatically when lack of water 2)Fog can spary with different frequencies 3)controlled by the Timer			
	< 7µm	12 hours	72*40*40, 53kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	   									
260m nylon hose, 260 nozzles and 261 slip lock connectors											

PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2805B, 3WZ-1810	fog machine, mist system	11L/min, SS cover, no digital timer, crank pump (3 plungers)	220V/380V	50Hz/60Hz	2.2KW	60Bar, 860PSI	4-10°C	11L/min	800m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger			
	< 7μm	12 hours	72*40*40, 50kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package	   									
160m nylon hose, 160 nozzles and 161 slip lock connectors		DLQ-6062									

PICTURE OF MISTING SYSTEM	DESCRIPTION OF COMMODITY										
	Model	Name	Description	Voltage	Frequency	Pump Motor Power	Pump Pressure	Drop the Temperature	Water Flow Rate	Spray Effective Area	
	PC-2805C, 3WZ-1814	fog machine, mist system	15.4L/min, SS cover, no digital timer, crank pump (3 plungers)	220V/380V	50Hz/60Hz	3KW	60Bar, 860PSI	4-10℃	15.4L/min	1000m ²	
	Diameter of Fog	Spray Sustainable Time	Dimension and Weight	Certification	MOQ	Lead time	Package	Feature: 1)Forged brass manifold 2)NSK bearing 3)Italian seal 4)First-grade ceramic plunger			
	< 7μm	12 hours	72*40*40, 53kgs	CE	min 50PCS	15 days after payment	1 cartons/unit				
Accessories	Pictures of the Accessories and the Package										
260m nylon hose, 260 nozzles and 261 slip lock connectors	    <p style="text-align: center;">DLQ-6062</p>										