

额定电压DC6V测试规格参数表

减速比 (变比)	4.4	9.6	21.3	35	46	78	103	171	226	377	500
空载电流 MA	≤100	≤100	≤100	≤100	≤100	≤100	≤100	≤100	≤100	≤100	≤100
空载转速 rpm	1360	620	280	170	130	77	60	35	26	16	12
额定转矩 Kg.cm	0.1	0.22	0.5	0.8	1.0	1.8	2.4	4.0	5.2	8.4	9.0
额定转速 rpm	1000	450	220	130	100	60	46	27	20	12	9
额定电流 A	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45
最大转矩 Kg.cm	0.35	0.75	1.7	2.8	3.6	6.2	8.2	9.0	最大承受9KG		
停转电流 A	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	不允许堵转		
L长度mm	17		19	21		23		25		27	

额定电压DC12V测试规格参数表

减速比 (变比)	4.4	9.6	21.3	35	46	78	103	171	226	377	500
空载电流 MA	≤60	≤60	≤60	≤60	≤60	≤60	≤60	≤60	≤60	≤60	≤60
空载转速 rpm	1360	620	280	170	130	77	60	35	26	16	12
额定转矩 Kg.cm	0.1	0.22	0.5	0.8	1.0	1.8	2.4	4.0	5.2	8.4	9.0
额定转速 rpm	1000	450	220	130	100	60	46	27	20	12	9
额定电流 A	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45	≤0.45
最大转矩 Kg.cm	0.35	0.75	1.7	2.8	3.6	6.2	8.2	9.0	最大承受9KG		
停转电流 A	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	不允许堵转		
L长度mm	17		19	21		23		25		27	

额定电压DC24V测试规格参数表

减速比 (变比)	4.4	9.6	21.3	35	46	78	103	171	226	377	500
空载电流 MA	≤40	≤40	≤40	≤40	≤40	≤40	≤40	≤40	≤40	≤40	≤40
空载转速 rpm	1360	620	280	170	130	77	60	35	26	16	12
额定转矩 Kg.cm	0.1	0.22	0.5	0.8	1.0	1.8	2.4	4.0	5.2	8.4	9.0
额定转速 rpm	1000	450	220	130	100	60	46	27	20	12	9
额定电流 A	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25
最大转矩 Kg.cm	0.35	0.75	1.7	2.8	3.6	6.2	8.2	9.0	最大承受9KG		
停转电流 A	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	不允许堵转		
L长度mm	17		19	21		23		25		27	

