

TR-HUM1A4 溼度傳送器



- 測量範圍: 10 ~ 95%R.H.
- 輸出: 直流 4 ~ 20mA
- 附溼度測棒一只
- 工作電壓: AC90V ~ 264V (50/60HZ)
- 外部調整: 歸零及斜率調整

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Measure Range	10 %RH to 95 %RH
Output	4 - 20 mA
	10 %RH = 5.6 mA
	50 %RH = 12 mA
	95 %RH = 19.2 mA
External Adjustment	ZERO VR , SPAN VR
Power Supply	90 - 260 ACV/ 50 Hz/60 Hz
Operation Temperature	0 - 50 °C (32 - 122 °F)
Operation Humidity	Less than 80 %RH

Accessory Included	Humidity probe
Optional Accessories	33% RH Humidity calibrator, RHA-33A 75% RH Humidity calibrator,RHA-75A
Mounting	Din rail or Wall
Case	ABS plastic
Others	Separate probe with plug

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)