



勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**951DX**

### LONER Deluxe Soldering Station

Low voltage soldering station



- 24V hand tool meets low voltage requirements
- Accurate temperature control
- External calibration helps with ISO9000 compliance
- Modular assembly of parts for easy maintenance
- Wide variety of soldering and SMT CROWN tips available
- Detachable handles for easy replacement



**951DP**

### LONER Deluxe High Performance Soldering Station

- 24V high performance hand tool
- Direct tip-heater configuration results in quick heat-up and recovery
- Accurate temperature control
- External calibration helps with ISO9000 compliance
- Modular assembly of parts for easy maintenance
- Wide variety of soldering and SMT CROWN tips available



**971DX**

### LONER Deluxe High Performance Temperature Controlled Soldering Station



- 24V hand tool
- Direct tip-heater configuration results in quick heat-up and recovery
- Advanced circuit design provides precise temperature control and external calibration
- Fume extraction and hot air conversion kits (sold separately) offer economy and versatility
- New front loading design makes tip change faster and easier

## Specifications for Model 951DX



**Power Requirements**  
**Power Rating**  
**Heater Rating**

**Weight**

**Overall Dimension**

**Temperature Range**

**Temperature Regulation**

**Tip-to-Ground Voltage  
Leakage/Resistance**

| 951DX-100                            | 951DX-230                            | Options for 951DX-230               |  |
|--------------------------------------|--------------------------------------|-------------------------------------|--|
| 100V, 50Hz<br>18W - 160W<br>24V, 53W | 230V, 50Hz<br>18W - 160W<br>24V, 53W | 951DX-230B<br>British Standard Plug |  |
|                                      |                                      | 951DX-230P<br>No Plug               |  |
|                                      |                                      | 1.8 kg                              |  |
|                                      |                                      | 104 mm x 216 mm x 254 mm            |  |
|                                      |                                      | 205°C-427°C                         |  |
|                                      |                                      | < 2mV/< 2 ohms                      |  |
|                                      |                                      | ±3°C                                |  |

## Specifications for Model 951DP



**Power Requirements**  
**Power Rating**  
**Heater Rating**

**Weight**

**Overall Dimension**

**Temperature Range**

**Temperature Regulation**

**Tip-to-Ground Voltage  
Leakage/Resistance**

| 951DP-100                            | 951DP-230                            | Options for 951DP-230               |  |
|--------------------------------------|--------------------------------------|-------------------------------------|--|
| 100V, 50Hz<br>17W - 170W<br>24V, 45W | 230V, 50Hz<br>17W - 170W<br>24V, 45W | 951DP-230B<br>British Standard Plug |  |
|                                      |                                      | 951DP-230P<br>No Plug               |  |
|                                      |                                      | 1.8 kg                              |  |
|                                      |                                      | 104 mm x 216 mm x 254 mm            |  |
|                                      |                                      | 205°C-427°C                         |  |
|                                      |                                      | < 2mV/< 2 ohms                      |  |
|                                      |                                      | ±3°C                                |  |

## Specifications for Model 971DX



**Power Requirements**  
**Power Rating**  
**Heater Rating**

**Weight**

**Overall Dimension**

**Temperature Range**

**Temperature Regulation**

**Tip-to-Ground Voltage  
Leakage/Resistance**

| 971DX-100                            | 971DX-230                            | Options for 971DX-230               |  |
|--------------------------------------|--------------------------------------|-------------------------------------|--|
| 100V, 50Hz<br>18W - 160W<br>24V, 53W | 230V, 50Hz<br>18W - 160W<br>24V, 53W | 971DX-230B<br>British Standard Plug |  |
|                                      |                                      | 971DX-230P<br>No Plug               |  |
|                                      |                                      | 1.8 kg                              |  |
|                                      |                                      | 104 mm x 216 mm x 254 mm            |  |
|                                      |                                      | 205°C-427°C                         |  |
|                                      |                                      | < 2mV/< 2 ohms                      |  |
|                                      |                                      | ±3°C                                |  |

勝特力科技 886-3-5753170  
勝特力电子 86-755-83289224  
[Http://www.100y.com.tw](http://www.100y.com.tw)