



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## DB9 M-M Cable (9C) Molded, 15 ft.

### Key Features

- With DB9 cables you will no longer sacrifice convenience when it comes to the placement of computer peripherals in your work area! Let us give you the flexibility to add an additional piece of hardware wherever you need it. Our DB9 cables can allow you to add your peripherals to an application or replace the cables that restrict you. Each DB9 cable comes fully shielded to prevent unwanted EMI/RFI interference, and its fully-molded design delivers excellent strain relief.

### Specification

#### • Details:

##### **Cable:**

Length: 15ft

Connectors: 2x DB9-Male

Conductors: 28 Awg (7/0.12)

Color: Beige Jacket

##### **Materials:**

Contacts: Gold Flash 1u" min.

Shell: Tin-Plated

Wire Insulation: PVC

Foil Sheild: Aluminum Mylar

Jacket: PVC

Insulator Material: Polyester Resin & Glass Fiber Reinforced (UL94V--0)

##### **Electrical:**

Current Rating: 1 Amp

Dielectric Withstanding Voltage: AC 500V (for 1 minute)

Insulation Resistance: 1000MOhm Min. @ 500V DC

Contact Resistance: 15MOhms Max. Mated

Working Temperature: -55 deg. C to 105 deg. C


- **Safety:** UL94V--0

### Technical Drawings / Photos

DB9 Male



DB9 Male



#### Pin Configuration:

DB9	DB9
Gr	~ Gr
1	~ 1
2	~ 2
3	~ 3
4	~ 4
5	~ 5
6	~ 6
7	~ 7
8	~ 8
9	~ 9