



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



CONTACT CONFIGURATION

Code	Bushing & Button Material
B2	Nickel plated brass with varnished polished
B21	Gold plated brass with varnished polished
B22	Stainless steel with varnished polished

SPECIFICATIONS:

- 1.Contact Rating: 2A @ 36VDC.
- 2.Electrical Life: 200,000cycles.
- 3.Contact Resistance: 50m-ohms max (initial).
- 4.Insulation Resistance: 1,000M-ohms min @ 500VDC.
- 5.Dielectric Strength: 2,000V RMS 50~60Hz.
- 6.Operating Temperature: -20°C ~ +70°C.
- 7.Switching Circuit: OFF-MOM.
- 8.IP Class: IP65 protection.
- 9.Torque: 5~14Nm max. applied to nut.
- 10.Operating Force: 5.5N max.

MATERIALS:

- 1.Bushing & Button: Refer to above table
- 2.Contact: Silver alloy.
- 3.Nut: Nickel plated brass.
- 4.Base: PBT.

ITEM NO. 料號	AV01-B2(B2x)-M1-R B22
----------------	--------------------------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1°		USED 規格	AV
DIMENSIONS TOLERANCE		FINISH 處理	
0.00 TO 30.00mm	±0.20mm	SCALE 比例	2 / 1 UNIT 單位 in(mm)
30.01 TO 60.00mm	±0.25mm	TITLE 名稱 Anti-Vandal Switch	
60.01 TO 150.00mm	±0.30mm		
150.01 TO 300.00mm	±0.40mm	DWG NO. 圖號	AV01-B2(B2x)-M1-R
MATERIAL		FILE NAME 檔案名稱	AV01B2M1R.DWG
		SHEET 張	1 / 1
		REV. 修改	1
		SIZE 規格	A4