



FEP TEFLON HIGH TEMP. WIRE



UL FILE No.E208889 UL AWM Style # 1332

Specification :

- **Conductor :**
Solid and Stranded Tinned Copper
- **Insulation :**
FEP TEFLON
- **Wall Thickness :**
0.33mm
- **Temperature Rating :**
UL 200° C
- **Voltage Rating :**
UL 300 V
- **Colors :**
White, Red, Orange, Yellow, Green, Blue, Black, Gray, Brown, Violet



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

FEP WIRE "UL1332" 200°C 300V

CONDUCTOR(導體)		INSULATION(絕緣體)		
尺寸 SIZE	股數/線徑 STRANDING	直徑 DIA.	厚度 THICKNESS	完成外徑 OUTER DIA.
AWG	NO./mm	mm	mm	mm
32	1/0.203	0.203	0.33	0.863
	7/0.079	0.237	0.33	0.897
	19/0.051	0.255	0.33	0.915
30	1/0.254	0.254	0.33	0.914
	7/0.102	0.306	0.33	0.966
	19/0.064	0.32	0.33	0.98
28	1/0.320	0.32	0.33	0.98
	7/0.127	0.381	0.33	1.041
	19/0.079	0.395	0.33	1.055
26	1/0.404	0.404	0.33	1.064
	7/0.160	0.48	0.33	1.14
	19/0.102	0.51	0.33	1.17
24	1/0.511	0.511	0.33	1.171
	7/0.203	0.609	0.33	1.29
	19/0.127	0.35	0.33	1.295
22	1/0.643	0.43	0.33	1.303
	7/0.254	0.762	0.33	1.422
	19/0.160	0.8	0.33	1.46
20	1/0.813	0.813	0.33	1.473
	7/0.320	0.9	0.33	1.62
	19/0.203	1.02	0.33	1.68
18	1/1.024	1.024	0.33	1.684
	7/0.404	1.21	0.33	1.87
	19/0.254	1.27	0.33	1.97
16	1/1.290	1.29	0.33	1.95
	7/0.5	1.5	0.33	2.1
	19/0.32	1.6	0.33	2.26

*Package: Every 610 meter per roll