




勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- NOTES:
- SPECIFICATION
- 1.Current Rating: 3A
 - 2.Withstanding Voltage: 500 VAC (1 min.)
 - 3.Insulation Resistance: 1000 Megohms MIN.
 - 4.Contact Resistance: 30 Milliohms MAX.
 - 5.Operating Temperature: -40°C to +85°
 - 6.Retention Force: 1Kg MIN.

- MATERIAL
- 1.Contact: Brass,
0.64mm Square pin
 - 2.Insulator: P.B.T. + 30% G.F.
 - 3.Plated: Gold Flash

ORDERING INFORMATION

BHDRB-2 XX 01B000

NO. OF CONTACT

DIMENSION IN mm [Inch]		PROD. SPEC.	C	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TITLE	
.X±0.30	X.*±	APPROVE	HEADER MALE 2.54mm BOX D/R R/A	CUSTOMER DRAWING
.XX±0.20	.X.*±	CHECK	FILE NO.	DWG NO. BHDRB-2XX01B000
.XXX±	.XX.*±	DRAW	SIZE A4	PROJ. SHEET 1 / 1
			SCALE 2.5:1	REV A