


Ceramic Disc Capacitor

Class 1 Temperature Compensation

Features

- Linear Temperature coefficient of capacitance
- High Stability of capacitance
- Low loss at wide range of frequency



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specification	
Operating Temperature Range	-25°C to +85°C
Rated Working Voltage	DC 50V, 500V
Test Voltage	3 times of the rated voltage
Capacitance	Within the tolerance at 1MHz, 1±0.2 Vrms, 25°C
Q Factor	At 1Mhz: 1±0.2 Vrms, 25°C C > 30pF Q > 1,000 C < 30pF Q ≥ 400+20°C (C: Rated capacitance)
Insulation Resistance	10,000M ohm min.

Rated Volt. (VDC)	Temp. Char.	Capacitance		Dimensions (mm)		
		Range (pF)	Tolerance	D max	T max	F
50	CH 0±60 PPM/°C (NPO)	0.5 ~ 47	±0.5pF (under 10 pF)	5.5	3.5	5.0
		50 ~ 75		6.5		
		82 ~ 100		7.5		
		120 ~ 150	±5% & ±10% (Over 10 pF)	8.5		5.0, 10.0
		180 ~ 270		10.5		
		300 ~ 390		12.5		
50	SL +350 ~ -1000 PPM/°C	10 ~ 120	±5% & ±10%	5.5	3.5	5.0
		150 ~ 240		6.5		
		270 ~ 330		7.5		
		360 ~ 470		8.5		
		500 ~ 820		10.5		

Class 2 High Dielectric Constant

Features

- Large capacitance in small size
- Non liner temperature coefficient of capacitance

Specification	
Rated Working Voltage	DC 50V, 500V

Test Voltage

2.5 times of the rated voltage

Capacitance

Within the tolerance at 1MHz, 1 ± 0.2

Dissipation Factor

 V_{rms} , 25°C

Dissipation Factor

Y5P, Z5U : $\tan \delta < 2.5\%$

Insulation

Z5V : $\tan \delta < 5\%$

Resistance

10,000M ohm or 200M ohm μF ,
whichever is the smallerRated
Volt.
(VDC)Temp.
Char.

Capacitance

Dimensions (mm)

Range
(pF)

Tolerance

D max

T max

F

50

B
 $\pm 10\%$
(Y5P)

100 ~

2000

2000 .

2700

3000 .

3300

3900 .

4700

5600 .

6800

10000

2200 .

3300

4700 .

5000

4600 .

6800

8200

10000

12000 .

15000

18000 .

20000

22000

4700 .

5000

10000 .

15000

18000 .

20000

20000 .

30000

33000 .

40000

 $\pm 10\%$ &
 $\pm 20\%$

5.5

6.5

7.5

8.5

10.5

5.5

6.5

7.5

8.5

10.5

5.5

6.5

7.5

8.5

10.5

3.5

3.5

3.5

5.0

5.0

5.0

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Class 3 Semi Conductive Type

Features

- Linear Temperature coefficient of capacitance
- Stable capacitance change over the specified temperature
- Low loss at wide range of frequency
- Cost saving by replacing film capacitors.
- Ultra large capacitance in small size

Specification

Operating Temperature Range -10°C to +85°C
 Rated Working Voltage DC 16V, 25V, 50V
 Test Voltage 2 times of the rated voltage
 Dissipation Factor At 1Mhz: 0.1 Vrms, 25°C
 Factor (tan δ)
 FY 16V 7.5%max
 FY. RY 25/50 5%max
 Insulation Resistance (at 25°C)
 16V, 100M ohm μ F or M ohm μ f
 whichever is less
 25V/50V, 1000M ohm μ F or 20 M ohm μ F
 whichever is less

Rated Volt. (VDC)	Temp. Char.	Capacitance		Dimensions (mm)		
		Range (pF)	Tolerance	D max	T max	F
50	FY +22 ~ 82% (Y5V)	20000 ~ 100000	$\pm 20\%$ & +80-20%	5.5	3.5	5.0
		20000 ~ 220000		10.5		
		22000		5.5		
		33000 ~ 100000		6.5		
50	RY $\pm 15\%$ (Y5R)	200000 ~ 220000	± 10 & $\pm 20\%$	10.5	3.5	5.0
		22000		5.5		
		33000 ~ 47000		6.5		
		100000		5.5		
50	RY $\pm 15\%$ (Y5R)	6800 ~ 10000	± 10 & $\pm 20\%$	5.5	3.5	5.0
		15000 ~ 22000		6.5		
		33000 ~ 47000		7.5		
		68000 ~ 100000		8.5		
50	RY $\pm 15\%$ (Y5R)	68000 ~ 10000	± 10 & $\pm 20\%$	5.5	3.5	5.0
		15000 ~ 22000		6.5		
		33000 ~ 47000		8.5		
		68000		10.5		

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)