

2.54MM MINI JUMPER

MATERIAL

INSULATOR : 30% Glass fiber PBT

CONTACT PIN : Brass

Phosphor bronze

SPECIFICATION

CURRENT RATE : 1 AMP

INSULATION RESISTANCE : 5000MΩ Min.

CONTACT RESISTANCE : 20mΩ Max.

DIELECTRIC VOLTAGE : 500V AC for one minute

OPERATION TEMPERATURE : -55°C to +105°C




勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)

1. B: Brass
P: Phosphor bronze
2. A: Close 6.5mm
B: Open 6.0mm
C: Open 4.5mm
D: Open with handle 13.5mm
3. G: Gold flash
T: Tin plated
4. B: Black Insulator
W: White Insulator
U: Blue
G: Gray
R: Red
Y: Yellow
E: Green



unit:mm

圖名 MOLD NAME		2.54mm Mini Jumper Open B type			
圖號 DRAWING NO.				比例 SCALE	FREE
公差 TOLERANCE		±0.2	繪圖 DRAW BY	日期 DATE	011017