

# 15W DC-DC Dual Output

- 2:1 input range
- Excellent regulation
- Input LC filter
- Short circuit protection
- Over current protection
- 100% burn-in test
- Free air convection



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Specification

Voltage accuracy.....	± 2%
Line regulation.....	± 0.3%
Load regulation.....	± 2% (20%~full load)
Efficiency.....	>76% @ full load, nominal I/P
I/O isolation voltage.....	500VDC MIN.
I/O isolation resistance.....	100MW MIN.
Operating temperature.....	-15 °C to +60 °C (no derating)
Storage temperature.....	-25 °C to +85 °C ♂J
Temp. Coefficient.....	± 0.02%/ ♂J
EMI/RFI.....	Six sided shield metal case

## ❖ Dual output

Part No	Input (VDC)	Output (VDC)	Current (mA)	Ripple p-p(mV)
DKE15A-05	9~18	±5	±1500	50
DKE15A-12	9~18	±12	±625	60
DKE15A-15	9~18	±15	±500	60
DKE15A-24	9~18	±24	±313	8
DKE15B-05	18~36	±5	±1500	50
DKE15B-12	18~36	±12	±625	60
DKE15B-15	18~36	±15	±500	60
DKE15B-24	18~36	±24	±313	80
DKE15C-05	36~72	±5	±1500	50
DKE15C-12	36~72	±12	±625	60
DKE15C-15	36~72	±15	±500	60
DKE15C-24	36~72	±24	±313	80