

ER34615M Lithium Thionyl Chloride Battery

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Brief Datasheet

1 Basic Specification


(Typical values relative to cells stored for one year or less at +30 °C max.)

Nominal capacity (at10mA +23°C,2.0V cut off)	14000mAh
Nominal voltage	3.6V
Standard discharge current	10mA
Maximum continuous current	2000mA
Maximum pulse current	3000mA
Operating temperature range	-55°C- +85°C
Storage temperature (recommended)	+30 °C Max
Weight	118g




*High power type is spiral structure and best suit for high current discharge.

*Underwriters Laboratories (UL) Component Recognition (File Number MH 20555).

2 Dimension



3 Electrical Characteristics





HI-POWER TYPE


-VX Pin

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)


-VXR Pin



-VB Pin







-VBR Pin



-VY Pin



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

-FT Pin



-AV(Axial Pin)

-AX(Axial Pin)



- LD(Cable)

- LD/(With connector)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

