

▼ 306D AUTOMATIC RESET WRENCHES WITHOUT ACCESSORIES

▷ ISO 6789.

- Accuracy ex works: $\pm 2\%$ except:
- K.315DA, K.325D: $\pm 4\%$.
- R.304DA: $\pm 6\%$.
- Reliability of mechanism: 50 000 cycles
- For use with removable accessories, such as open end and ring end, or with ratchets.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Model	Capacity N.m	End fitting	Graduation N.m	Dimensions (wrench only)		Case	Dimensions (with box)	
				L (mm)	$\Delta\Delta$ kg		L (mm)	$\Delta\Delta$ kg
R.304DA	1-5	9 x 12	0,05	185	0,290	BP.D1	420	0,77
R.306-25D	5-25	9 x 12	0,10	254	0,41	BP.D1	420	0,9
J.306-50D	10-50	9 x 12	1,00	347	0,89	BP.D2	585	1,54
S.306-100D	20-100	9 x 12	1,00	437	1,05	BP.D2	585	1,75
S.306-200D	40-200	14 x 18	1,00	515	1,26	BP.D3	805	2,22
S.306-350D	70-350	14 x 18	2,00	725	1,79	BP.D3	805	2,75
K.315DA	120-600	14 x 18	2,00	945	4,6	BT.121A	1050	8,8
K.325DA	200 - 1000	Ø 30	4,00	1280	5,9	BT.K325D	1420	11,77