

HAKKO FX-951ESD 無鉛用烙鐵

Standard Soldering Iron for Lead-free Soldering



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

特點

強力的熱回復性：以更低的設定溫度即可進行焊接

睡眠開關機能：無進行作業而閒置時，先前的溫度會自動下降至 200 ℃，以減輕之前的負荷

溫度管理機能：以專用卡片固定設定溫度

可設定下限溫度，並可利用數位複位方式，簡單進行溫度修正

安全設計：防靜電規格

電熱裝置斷線等各種錯誤情形時，會發出風鳴警報

規格(HAKKO FX-951)

功率消耗	75W
溫度範圍	200 450 ℃(400~840 ℉)
溫度穩定度	非使用狀態時為±5 ℃(±9 ℉)

控制臺

輸出	24V
外形體積	80(W) x 130(H) x 131(D) mm
重量	1.2kg

焊鐵(FM-2025)


功率消耗	70 W
標準焊鐵頭	T12 系列
焊鐵頭至接地電阻	2Ω 以下
焊鐵頭至接地電勢	2mV 以下
長度(不包括電線)	188mm (附 2.4D 焊鐵頭)
重量(不包括電線)	30g (附 2.4D 焊鐵頭)
電線組件	1.2m

Tip Shapes


勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Shape-B

T12-B SHAPE-B



T12-B2 SHAPE-0.5B



T12-B3 SHAPE-0.7B



T12-B4 SHAPE-0.4B




T12-BL SHAPE-BL




Shape-BC

T12-BC1 SHAPE-1BC




* Tinned on the soldering surface only.

T12-BC2 SHAPE-2BC




T12-BC3 SHAPE-3BC




Shape-C

T12-C1 SHAPE-1C




* Tinned on the soldering surface only.

T12-C4 SHAPE-4C




Shape-D


T12-D08 SHAPE-0.8D




T12-D12 SHAPE-1.2D




T12-D16 SHAPE-1.6D




T12-D24 SHAPE-2.4D




T12-D4 SHAPE-4D




T12-D52 SHAPE-5.2D




T12-DL08 SHAPE-0.8DL




T12-DL12 SHAPE-1.2DL



T12-DL32 SHAPE-3.2DL




T12-DL52 SHAPE-5.2DL




Shape-I

T12-I SHAPE-I



T12-IL SHAPE-IL




T12-ILS SHAPE-ILS



Shape-J

T12-J02 SHAPE-0.2J



T12-JL02 SHAPE-0.2JL




T12-JS02 SHAPE-0.2JS




Shape-K


T12-K SHAPE-K




T12-KF SHAPE-KF




T12-KL SHAPE-KL



T12-KR SHAPE-KR






T12-KU SHAPE-KU





勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)


T12-B2Z SHAPE-0.5B (Z)

T12-BC1Z SHAPE-1BC (Z)
T12-BCF1Z*T12-BC2Z SHAPE-2BC (Z)
T12-BCF2Z*T12-BC3Z SHAPE-3BC (Z)
T12-BCF3Z*


T12-BZ SHAPE-B (Z)

T12-C4Z SHAPE-4C (Z)
T12-CF4Z*


T12-D12Z SHAPE-1.2D (Z)




T12-D16Z SHAPE-1.6D (Z)




T12-D24Z SHAPE-2.4D (Z)




T12-D4Z SHAPE-4D (Z)



T12-KFZ SHAPE-KF (Z)





T12-KRZ SHAPE-KR (Z)



* Tinned on the soldering surface only.

C cut with indent

T12-BCM2 SHAPE-2BC
Bevel with indentT12-BCM3 SHAPE-3BC
Bevel with indent

* The T12-BCM2 and T12-BCM3 tips are not available for sale or use in the U.S.A.
Do not bring them into the U.S.A.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)