

FCD

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Stage Studio Theater TV (Medium Type)

image

GX9.5 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
FCD 100V 300W B/L		100	300	20	110	70	6600	3050	300	C-13	1
FCD 100V 500W B/SP		100	500	20	95	55	9500	3050	500	C-13	2
FCD 100V 500W C/SP		100	500	20	95	55	12000	3200	200	C-13	2
FCD 100V 500WB/L		100	500	20	110	70	11500	3050	500	C-13	1
FCD 100V 500WC/L		100	500	20	110	70	13000	3200	200	C-13	1
FCD 100V 500WB/M		100	500	34	100	55.5	11000	3050	500	C-13	3
FCD 100V 500WC/M		100	500	30	100	55.5	13500	3200	200	C-13	3

E26 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
FCD 100V 500W/E		100	500	20	115	76	11000	3050	500	C-13	4

GY9.5(GZ9.5) Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
FCD 100V 300W C/S		100	300	20	80	46.5	7500	3200	100	C-13	5
FCD 100V 300W B/S		100	300	15	78	46.5	6200	3100	200	C-13	5
FCD 100V 500W B/SS		100	500	20	82	46.5	11000	3050	300	C-13	5
FCD 100V 500W C/SS		100	500	20	82	46.5	13000	3200	100	C-13	5
JCP 100V 500W		100	500	19.5	76	36.5	13500	3200	75	C-13D	5
EHA 100V 500W	EHA	100	500	19.5	76	36.5		3200	75	*C-13D	6
EHA 120V 500W	EHA	120	500	19.5	76	36.5		3200	75	*C-13D	6
EGZ 120V 500W	EGZ	120	500	19.5	76	36.5		3200	100	*C-13D	6
EMG 220V 500W	EMG	220	500	19.5	76	36.5		3100	75	*C-13D	6
JCP 220/230V 500W		225	500	23	76	36.5	13000	3250	75	C-13	5
JCP 240/250V 500W		245	500	23	76	36.5	13000	3250	75	C-13	5
DZT 100V 625W	DZT	100	625	19.5	89	44.5		3350	75	*C-13D	7
BVE 120V 625W	BVE	120	625	19.5	89	44.5		3350	75	*C-13D	7
DZV 220V 625W	DZV	220	625	23	89	44.5		3250	50	*C-13D	8
DZV 240V 625W	DZV	240	625	23	89	44.5		3250	50	*C-13D	8
FCD 100V 650W C/S		100	650	82	20	46.5	16800	3200	100	C-13	5
FCD 100V 650W B/S		100	650	82	20	46.5	14300	3050	500	C-13	5
JCP 100V 650W		100	650	19.5	76	36.5	18750	3300	75	C-13D	5
JCP 220/230V 650W		225	650	23	76	36.5	17750	3250	75	C-13	5
JCP 240/250V 650W		245	650	23	76	36.5	17750	3200	75	C-13	5
JCP 100V 750W		100	750	23	95	44.5	21000	3250	100	C-13D	5
BVA 120V 900W	BVA	120	900	23	95	44.5		3300	75	*C-13D	6
JCP 100V 1000W		100	1000	23		44.5	28500	3250	100	C-13D	5

					95						
JCP 120V 1000W	BTA	120	1000	23	95	44.5	28500	3250	100	C-13D	5

*C-13D denotes proximity reflector

L M S denote a different light center length

G22 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
FCD 100V 650WC		100	650	34	140	63.5	16800	3200	100	C-13	9

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)