

# J

## General Lighting - Double Ended Type

image



### R7s Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
J 220/230V 100WS		225	100	80.3	74.9	9	1200	2700	1500	C-8	1
J 100V 150W		100	150	119.6	114.2	9	2400	2900	2000	C-8	1
J 120 150WS		120	150	80.3	74.9	12	2530	2900	1500	C-8	1
J 220/230V 150WS		225	150	80.3	74.9	12	1950	2750	1500	C-8	1
J 100V 200W		100	200	119.6	114.2	9	3400	2900	2000	C-8	1
J 120 250W		120	250	119.6	114.2	9	4000	2900	2000	C-8	1
J 220/230V 250W		225	250	119.6	114.2	9	4000	2850	1500	C-8	1
J 240/250V 250W		245	250	119.6	114.2	9	4000	2900	1500	C-8	1
J 100V 300W		100	300	119.6	114.2	9	6000	2950	2000	C-8	1
J 120V 300W	EHM	120	300	119.6	114.2	9	6000	2950	2000	C-8	1
J 220/230V 300W		225	300	119.6	114.2	9	5000	2900	2000	C-8	1
J 240/250V 300W		245	300	119.6	114.2	9	5000	2900	2000	C-8	1
J 100V 500W		100	500	119.6	114.2	12	11000	3000	2000	C-8	1
J 120V 500W	FCL	120	500	119.6	114.2	12	11000	3000	2000	C-8	1
J 220/230V 500W	BSH	225	500	119.6	114.2	12	9500	2950	2000	C-8	1
J 240/250V 500W	BSH	245	500	119.6	114.2	12	9500	2950	2000	C-8	1
J 220/230V 750W		225	750	191.1	185.7	12	16500	3000	2000	C-8	1
J 240/250V 750W		245	750	191.1	185.7	12	16500	3000	2000	C-8	1
J 120V 1000W		120	1000	191.1	185.7	12	22000	3000	2000	C-8	1
J 220/230V 1000WL		225	1000	256.1	250.7	12	21000	3000	2000	C-8	1
J 220/230V 1000W	DZX	225	1000	191.1	185.7	12	22000	3000	2000	C-8	1
J 240/250V 1000W	DZX	245	1000	191.1	185.7	12	22000	3000	2000	C-8	1
J 220/230V 1500W	DYE/DYD	225	1500	256.1	250.7	12	33000	3000	2000	C-8	1
J 240/250V 1500W	DYE/DYD	245	1500	258.1	250.7	12	33000	3000	2000	C-8	1
J 220/230V 2000W		225	2000	332.8	327.4	12	45000	3050	2000	C-8	1
J 240/250V 2000W		225	2000	332.8	327.4	12	45000	3050	2000	C-8	1

**勝特力材料 886-3-5753170**  
**勝特力电子(上海) 86-21-54151736**  
**勝特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)