

JCD

Optical - Coiled Coil

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



image

G5.3 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
GCA 120V 250W	GCA	120	250	11.5	57	32	7000	3200	50	CC-8	2
EYH/FKT 120V 250W	EYH/FKT	120	250	22	63	36.5	6050	3050	150	CC-6	1
FGB/FBD 120V 500W	FGB/FBD	120	500	22	76	44.5	13200	3200	50	CC-6	1
DYH 120V 600W	DYH	120	600	22	63	36.5	17000	3200	75	CC-6	1
DW 120V 650W	DVY	120	650	19.9	63	36.5	20000	3400	25	CC-6	1

G6.35,G6.35 Ceramic Cover Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JCD 25V 250W/SX		25	250	13.5	50	33	7500	3400	50	CC-6	3
JCD 100V 100W/SX		100	100	13.5	50	30	2100	3050	100	CC-6	3
JCD 120V 100W/SX		120	100	13.5	50	30	2000	3000	150	CC-6	4
JCD 100V 150W/CT		100	150	13.5	50	30	4250	3200	50	CC-6	3
JCD 100V 150W/SX		100	150	13.5	50	32	3300	3075	200	CC-6	3
JCD 120V 150W/SX	ESY	120	150	13.5	50	30	3300	3050	200	CC-6	3
JCD 120V 150W/CT		120	150	13.5	50	30	4100	3200	50	CC-6	3
JCD 100V 250W/SX		100	250	16	50	33	6000	3050	300	CC-6	3
JCD 100V 300W/SX		100	300	16	50	33	6600	3050	500	CC-6	3
DRA 120V 300W	DRA	120	300	16	50	33	6900	3100	300	CC-6	3

GX6.35 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JCD 100V 200WC/L		100	200	22	63	37	5000	3200	50	CC-6	5
JCD 24V 250WC/L		24	250	13	60.3	36.5	7500	3400	15	CC-6	7
JCD 100V 300W B/L		100	300	22	63	37	6700	3050	250	CC-6	5
JCD 100V 300WC/L		100	300	22	63	37	7500	3200	150	CC-6	5
JCD 120V 300WC/L		120	300	22	63	37	7500	3200	150	CC-6	5
JCD 100V500WB/L		100	500	22	63	37	11000	3050	250	CC-6	5
JCD 100V500WC/L		100	500	22	63	37	13000	3200	150	CC-6	5
JCD 100V 500WC/TL		100	500	20	65	37	13350	3200	200	CC-6	8
JCD 100V 650W B/L		100	650	22	63	37	14000	3050	250	CC-6	5
JCD 100V 650WC/L		100	650	22	63	37	17750	3200	150	CC-6	5
JCD 120V 650W/CL		100	650	22	63	37	17750	3200	75	CC-6	5
JCD 220/230V 650WL		225	650	24	63	37	16200	3200	50	2CC-8	6
JCD 240 250V/650WL		245	650	24	63	37	16200	3200	50	2CC-8	6

GX9.5 Base

Lamp Type	ANSI	Rated Voltages	Power Consumption	Outside Dimension			Total Lumen	Color Temp	Avg Life	Filament	Fig.No.

	(V)	(W)	A	B	C	(lm)	(K)	(H)		
JCD 24V 250WC/Z	24	250	13	58	35.5	7500	3400	50	CC-6	9
JCD 25V 250WC/Z	25	250	13	60.3	36.5	7000	3400	50	CC-6	9
JCD 100V 300WB/Z	100	300	22	63	37	6700	3050	250	CC-6	10
JCD 100V 300WC/Z	100	300	22	63	37	7500	3200	150	CC-6	10
JCD 100V 300WC/T	100	300	20	65	37	7500	3200	150	CC-6	11
JCD 100V 300WB/T	100	300	20	65	37	6700	3050	300	CC-6	11
JCD 100V 500WA/T	100	500	20	65	37	9000	2800	1000	CC-6	11
JCD 100V 500WB/T	100	500	20	65	37	11000	3050	500	CC-6	11
JCD 100V 500WC/T	100	500	20	65	37	13500	3200	200	CC-6	11
JCD 100V 650WB/T	100	650	20	65	37	14000	3050	500	CC-6	11
JCD 100V 650WC/T	100	650	20	65	37	16250	3200	200	CC-6	11
JCD 100V 650WS/T	100	650	20	65	37	20000	3400	25	CC-6	11
JCD 100V 1000WC/Z	100	1000	32	95	62	28000	3200	150	CC-6	12
JCD 100V 1000WB/Z	100	1000	32	95	62	24000	3050	800	CC-6	12

Z denotes GX9.5 base

GY9.5 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JCD 100V 300W B/C		100	300	22	63	36.5	6700	3050	250	CC-6	13
JCD 100V 300W C/C		100	300	22	63	36.5	7500	3200	150	CC-6	13
EKB 120V 420W	EKB	120	420	22	63	36.5	11000	3200	75	CC-6	13
JCD 100V 500W B/C		100	500	22	63	36.5	11000	3050	250	CC-6	13
JCD 100V 500W C/C		100	500	22	63	36.5	13000	3200	150	CC-6	13
JCD 120V 600W C/C	DVS/DYV/BHC	120	600	22	63	36.5	17000	3200	75	CC-6	13
JCD 125V 600W C/C	DYS-5	125	600	22	63	36.5	17000	3200	75	CC-6	13
JCD 100V 650W B/C		100	650	22	63	36.5	14000	3050	250	CC-6	13
JCD 100V 650W C/C		100	650	22	63	36.5	17750	3200	150	CC-6	13
JCD 120V 650W C/C		120	650	22	63	36.5	17750	3200	75	CC-6	13
EKD 120V 650W	EKD	120	650	19.9	66	36.5	20000	3400	25	CC-6	13
JCD 220/230V 650W/C	DYR	225	650	24	63	36.5	16200	3200	50	2CC-8	14
JCD 240/250V 650W/C	DYR	245	650	24	63	36.5	16200	3200	50	2CC-8	14

BA 15d Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
FEV 120V 200W		120	200	13.5	62	34.9	5500	3200	50	CC-2V	15

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)