

JCT

Optical - 4-pin Type

image

勝特力材料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



G17t-7 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
BCK 120V 500W	BCK	120	500	19.5	89	39.7	-	3250	50	*C-13D	2
CBA 120V 500W	CBA	120	500	-	92	44.5	-	3250	50	*C-13D	3
EGH 120V 500W	EGH/DYY	120	500	19.5	89	39.7	14000	3250	50	C-13D	1
EGX 120V 500W	EGX	120	500	-	92	44.5	-	3100	200	*C-13D	3
EPR 120V 500W	EPR	120	500	19.5	89	41	-	3250	50	*C-13D	4
EPS 220V 500W	EPS	220	500	19.5	89	41	-	3200	50	*C-13D	4
EPS 240V 500W	EPS	240	500	19.5	89	41	-	3200	50	*C-13D	4
JCT 100V 650W		100	650	19.5	85	39.7	16500	3200	150	C-13D	1
BRP 100V 750W	BRP	100	750	23	95	39.7	-	3300	50	*C-13D	2
BRP 120V 750W	BRP	120	750	23	95	39.7	-	3300	50	*C-13D	2
BRR 120V 1000W	BRR	120	1000	23	95	39.7	-	3250	50	*C-13D	2
BRN 120V 1200W	BRN	120	1200	23	95	39.7	-	3350	20	*C-13D	2
BTG 120V 1200W	BTG	120	1200	23	95	39.7	38200	3350	20	C-13D	1
BTG 120V 1200WF	BTG	120	1200	23	95	(*FROSTED BULB) 39.7	38000	3350	20	C-13D	1