

JPD

Stage Studio TheaterTV - Coiled Coil Double Ended

image



R7s Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
FCK 20V 170W	FCK	20	170	61.0	54.0	11	4250	3150	100	CC-8	1
DDN 20V 200W	DDN	20	200	61.0	54.0	11	5000	3150	100	CC-8	1
JPD 100V 300W C		100	300	80.3	74.9	14	7500	3200	150	CC-8	1
JPD 120V 300W G	EHP	120	300	80.3	74.9	14	5500	2900	2000	CC-8	1
JPD 30V 375W	DWZ	30	375	80.3	74.9	13.5	7500	2950	1000	CC-8	1
JPD 120V 400W G	EHR	120	400	80.3	74.9	14	6400	2900	2000	CC-8	1
JPD 100V 500W C		100	500	80.3	74.9	14	12500	3200	150	CC-8	1
JPD 100V 500W C/L		100	500	93.3	89.6	14	13000	3200	100	CC-8	1
JPD 100V 650W C		100	650	80.3	74.9	14	16200	3200	150	CC-8	1
JPD 120V 650W C	FAD	120	650	80.3	74.9	14	16500	3200	100	CC-8	1
JPD 120V 650W C/F	FBX	120	650	80.3	74.9	14	16000	3200	100	CC-8	1
JPD 240V 650W C		240	650	80.3	74.9	14	16300	3200	75	CC-8	1
JPD 240V 650W S		240	650	80.3	74.9	14	21000	3400	15	CC-8	1
JPD 100V 750W B		100	750	95.0	89.6	16	15800	3050	500	CC-8	1
JPD 230V 800W S	DXV	230	800	80.3	74.9	14	24800	3400	15	CC-8	1
JPD 240V 800W C	DXX	240	800	80.3	74.9	14	20000	3200	75	CC-8	1
JPD 240V 800W S	DXV	240	800	80.3	74.9	14	24800	3400	15	CC-8	1
JPD 100V 1000W C		100	1000	95.0	89.6	16	28000	3200	100	CC-8	1
JPD 100V 1000W B/L		100	1000	109.5	104.1	16	21000	3050	800	CC-8	1
JPD 100V 1000W C/L		100	1000	109.5	104.1	16	25000	3200	200	CC-8	1
JPD 120V 1000WC	BRH	12	1000	92.8	88.4	16	30000	3350	75	CC-8	1
JPD 120V 1000WC5	DXW	120	1000	95.0	89.6	16	28000	3200	150	CC-8	1
JPD 120V 1000WS1	DXN	120	1000	95.0	89.6	16	31000	3400	30	CC-8	1
JPD 220V 1000W C		220	1000	93.8	88.4	16	26000	3200	120	CC-8	1
JPD 240V 1000WC		240	1000	93.8	88.4	16	26000	3200	120	CC-8	1
JPD 120V 1050WS	ELJ	120	1050	119.6	114.2	16	30000	3200	75	CC-8	1

F denotes frosted bulb

RX7S Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JPD 120V 1000W C6	FER	120	1000	143.5	138.1	19	27500	3200	500	CC-8	2
JPD 100V 2000W		100	2000	142.9	138.4	25	57000	3200	300	CC-8	2
JPD 120V 2000W C	FEY	120	2000	142.9	138.4	28	57000	3200	300	CC-8	2
JPD 220V 2000W C	FEX	220	2000	142.9	138.4	28	50000	3200	300	CC-8	2
JPD 240V 2000W C	FEX	220	2000	142.9	138.4	28	50000	3200	300	CC-8	2

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)