

勝特力材料 886-3-5753170
勝特力電子(上海) 86-21-54151736
勝特力電子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



image

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Center Candlepower (cd)	Beam Angle (?)	Color Temp (K)	Avg Life (H)	Fig.No.
				Ref Dia (A)	MOL (B)					
JR12V20W NK3	FTB	12	20	35.3	40.0	3750	8	2950	2000	1
JR12V20W MK3	FTC	12	20	35.3	40.0	1360	19	2950	2000	1
JR12V20W WK3	FTD	12	20	35.3	40.0	900	30	2950	2000	1
JR12V35W NK3	FTE	12	35	35.3	40.0	4200	10	3050	3000	1
JR12V35W MK3	FTF	12	35	35.3	40.0	2350	20	3050	3000	1
JR12V35W WK3	FTH	12	35	35.3	40.0	1300	34	3050	3000	1

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Center Candlepower (cd)	Beam Angle (?)	Color Temp (K)	Avg Life (H)	Fig.No.
				Ref Dia (A)	MOL (B)					
JR12V20W NK5	ESX	12	20	50.7	46.0	4000	9	2950	3000	2
JR12V20W MK5	BBF	12	20	50.7	46.0	880	23	2950	3000	2
JR12V20W WK5	BAB	12	20	50.7	46.0	500	38	2950	3000	2
JR12V35W NK5	FRB	12	35	50.7	46.0	7600	12	3000	4000	2
JR12V35W MK5	FRA	12	35	50.7	46.0	2300	23	3000	4000	2
JR12V35W WK5	FMW	12	35	50.7	46.0	1100	38	3000	4000	2
JR12V50W NK5	EXT	12	50	50.7	46.0	9800	13	3050	4000	2
JR12V50W MK5	EXZ	12	50	50.7	46.0	3200	26	3050	4000	2
JR12V50W WK5	EXN	12	50	50.7	46.0	1600	38	3050	4000	2

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Center Candlepower (cd)	Beam Angle (°)	Color Temp (K)	Avg Life (H)	Fig.No.
				Ref Dia (A)	MOL (B)					
JR12V20W NK3EZ		12	20	35.3	55.0	3750	8	2950	2000	3
JR12V20W MK3EZ		12	20	35.3	55.0	1360	19	2950	2000	3
JR12V20W WK3EZ		12	20	35.3	55.0	900	30	2950	2000	3
JR12V35W NK3EZ		12	35	35.3	55.0	4200	10	3050	3000	3
JR12V35W MK3EZ		12	35	35.3	55.0	2350	20	3050	3000	3
JR12V35W WK3EZ		12	35	35.3	55.0	1300	34	3050	3000	3
JR12V35W NK5EZ		12	35	50.7	64.6	7600	12	3000	4000	4
JR12V35W MK5EZ		12	35	50.7	64.6	2300	23	3000	4000	4
JR12V35W WK5EZ		12	35	50.7	64.6	1100	38	3000	4000	4
JR12V50W NK3EZ		12	50	50.7	64.6	9800	13	3050	4000	4
JR12V50W MK3EZ		12	50	50.7	64.6	3200	26	3050	4000	4
JR12V50W WK3EZ		12	50	50.7	64.6	1600	38	3050	4000	4

[illegible]

JR12V20WKW/3B	FSV	12	20	35.3	46.5	570	30	2900	2000	5
JR12V35WKN/3B	GDX	12	35	35.3	46.5	5200	10	2950	2000	5
JR12V35WKM/3B	GDY	12	35	35.3	46.5	2300	20	2950	2000	5
JR12V35WKW/3B	GDZ	12	35	35.3	46.5	1200	30	2950	2000	5

勝 特 力 材 料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)