

JS

勝特力材料 886-8-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Stage Studio Theater TV (Large Type)

image

GX9.5 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JSH 100V 1000WB		100	1000	34	110	55	23000	3050	500	C-13	1
JSH 110V 1000W		110	1000	34	110	55	23000	3050	500	C-13	1
JS 100V 1000C/T		100	1000	22	135	90	27000	3200	200	CC-8	2
JS 100V 1000B/T		100	1000	22	135	90	23800	3050	500	CC-8	2
JS 100V 1000W B/U		100	1000	22	100	63.5	23000	3050	500	C-13	3

GX16 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JS 100V 1000W B/M		100	1000	30	140	85	23000	3050	500	C-13	4
JS 100V 1000W C/M		100	1000	30	140	85	27000	3200	200	C-13	4
JS 100V 1000W B/MP		100	1000	30	140	85	21000	3050	500	C-13	5
JS 100V 1000W C/MP		100	1000	30	140	85	24000	3200	200	C-13	5
JS 220V 1000W B/M		220	1000	30	140	85	23000	3050	500	C-13	4
JS 240V 1000W B/M		240	1000	30	140	85	23000	3050	500	C-13	4
JS 100V 1500W B/M		100	1500	35	140	85	34500	3050	500	C-13	4
JS 100V 1500W C/M		100	1500	35	140	85	42000	3200	200	C-13	4
JS 100V 1500W B/MP		100	1500	35	140	85	29500	3050	500	C-13	5
JS 100V 1500W C/MP		100	1500	35	140	85	35500	3200	200	C-13	5
JS 120V 1500W B/M		120	1500	35	140	85	34500	3050	500	C-13	4
JS 120V 1500W C/M		120	1500	35	140	85	39000	3200	300	C-13	4
JS 220V 1500W B/M		220	1500	35	140	85	31500	3050	500	C-13	4
JS 240V 1500W B/M		240	1500	35	140	85	31500	3050	500	C-13	4

GY16 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JS 110V 2000W C/S		110	2000	39	145	70	54000	3200	400	C-13	6

L M S denote a different light center length
 P denotes black coating

G22 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JS 100V 1KW B/SI		100	1000B	34	127	63.5	23000	3050	500	C-13	7
JS 100V 1000W C/SI		100	1000C	34	127	63.5	27000	3200	200	C-13	7
JS 100V 1000W B/S		100	1000B	34	135	75	23000	3050	500	C-13	7
JS 100V 1000W C/S		100	1000C	34	135	75	27000	3200	200	C-13	7
JS 100V 1500WB/S		100	1500	40	150	75	34500	3050	500	C-13	7

JS 100V 1500W C/S		100	1500	40	150	75	42000	3200	200	C-13	7
JS 100V 2000W B/S		100	2000B	39	176.5	90	48000	3050	500	C-13	8
JS 100V 2000W C/S		100	2000	39	176.5	90	56000	3200	300	C-13	8
JS 240V 1000W C/S		240	1000	34	140	63.5	26000	3200	200	C-13	7
EGN 120V 500W	EGN	120	500	19.5	140	63.5	13000	3200	100	C-13D	9
EGR 120V 750W	EGR	120	750	23	140	63.5	20000	3200	200	C-13D	9
EGT 120V 1000W	EGT	120	1000	23	140	63.5	27500	3200	200	C-13D	9
JCD 100V 2000WC		100	2000	40	165	105	56000	3200	200	CC-6	18

G38 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JS 120V1000W C/L	CYV	120	1000	22	196.9	127	27500	3200	200	C-13D	10
JS 100V 1500W C/L		100	1500	35	195	27	41000	3200	300	C-13	10
JS 100V1500WB/L		100	1500	35	195	127	34500	3050	500	C-13	10
JS 120V1500W C/L	CXZ	120	1500	35	203.2	127	38500	3200	325	C-13D	10
JS 100V2000W B/L		100	2000	45	200	127	48000	3050	500	C-13	10
JS 100V2000W C/L		100	2000	45	200	127	58000	3200	200	C-13	10
JS 120V 2000W	CYX	120	2000	45	215.9	127	59000	3200	250	C-13	10
BWA 120V 2000W	BWA	120	2000	25	203.5	127	54000	3200	500	CC-8	12
FKK 220/240V 2000W	FKK CP41	220/240	2000	50	200	127	52000	3200	400	C-13	10
JS 110/120V 2500WC		110/120	2500	45	250	165	65000	3200	400	C-13	10
JS 220V 2500W		220	2500	45	250	165	65000	3200	400	C-13D	10
JS 100V3000W B/M		100	3000	50	210	127	69000	3050	500	C-13	11
JS 100V3000W B/L		100	3000	50	230	148	69000	3050	500	C-13	10
JS 100V3000W C/M		100	3000	50	210	127	78000	3200	200	C-13	11
JS 100V3000W C/L		100	3000	60	230	148	78000	3200	200	C-13	10
JS 120V3000W C/M		120	3000	50	210	127	78000	3200	300	C-13	11
JS 220V3000W C/M		220	3000	50	200	127	78000	3200	300	C-13D	11
JS 100V 5000WB		100	5000	60	268	165	115000	3050	1000	C-13	13
JS 100V 5000WC		100	5000	60	268	165	145000	3200	500	C-13	13
DPY 120V 5000W	DPY	120	5000	60	268	165	140000	3200	500	C-13	13
CP 29 220/240V 5000W	CP29	220/240	5000	60	268	165	135000	3200	500	C-13	13
JS 100V 10000WC		100	10000	80	400	254	290000	3200	300	C-13	14
DTY 120V 10000W	DTY	120	10000	80	391	254	285000	3200	300	C-13	14
JS 220/240V10000W	CP83	220/240	10000	80	400	254	285000	3200	300	C-13	15
JS 100V 2000WC		100	12000	80	400	254	350000	3200	500	C13	14
JS 200V 20000WC		200	20000	100	550	354	520000	3250	400	C-13	16
JS 220V 20000WC		200	20000	100	550	354	580000	3200	400	C-13	16
JS 200V 24000W		200	24000	100	550	354	624000	3250	400	C-13	16

T89 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JS 100V 20000W		100	20000C	120	535	420	595000	3200	300	C-13	17

P28s Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					

EGC/EGD 120V500W	EGC/EGD	120	500	13.5	152	88.9	13000	3200	300	CC-8	19
BTL 120V 500W	BTL	120	500	19.5	127	55.5	11000	3050	500	C-13D	20
DNS/FMC 120VW 500W	DNS/FMC	120	500	19.5	156	88.9	11000	3050	500	C-13D	20
EGE 120V 500W	EGE	120	500	13.5	152	88.9	10000	3000	2000	CC-8	19
BTM 120V 500W	BTM	120	500	19.5	127	55.5	13000	3200	100	C-13D	20
EGF 120V 500W	EGF	120	750	16	152	88.9	20000	3200	250	CC-8	19
EGG 120V 750W	EGG	120	750	16	152	88.9	15000	3000	2000	CC-8	19
BTN 120V 750W	BTN	120	750	23	127	55.5	17000	3050	500	C-13D	20
DNT/FMD 120V 750W	DNT/FMD	120	750	23	156	88.9	17000	3050	500	C-13D	20
BTP 120V 750W	BTP	120	750	23	127	55.5	20000	3200	200	C-13D	20
*EGK 120V 1000W	EGK	120	1000	19.5	152	88.9	26500	3200	400	CC-8	19
BTP 120V 1000W	BTP	120	1000	23	127	55.5	27500	3200	200	C-13D	20
EGJ 120V 1000W	EGJ	120	1000	19.5	152	88.9	27500	3200	400	CC-8	19
DNV/FME 120V 1000W	DNV/FME	120	1000	23	156	88.9	27500	3200	200	C-13D	20

* ? ?

P40s Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
BVV 120V 1000W		120	1000	23	178	100	27500	3200	200	C-13D	21
BVT 120V 1000W		120	1000	23	178	100	23000	3050	500	C-13D	21

E39 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Total Lumen (lm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				A	B	C					
JS 100V1000W B/E		100	1000	30	145	105	23000	3050	500	C-13	22
JS 100V1000W C/E		100	1000	30	145	105	27000	3200	200	C-13	22
JS 100V1000W B/EL		100	1000	30	185	145	23000	3050	500	C-13	23
JS 100V1000W C/EL		100	1000	30	185	145	27000	3200	200	C-13	23
*JS/SD2 ?fi 100V1000WB		100	1000	165	360	252.5	22000	3050	400	C-7A	27
*JS/SD2 ?fi 100V1000WC		100	1000	165	360	252.5	26000	3200	200	C-7A	27
*JS/SR ? ? 100V1000WC		100	1000	165	360	252.5	26000	3200	200	C-7A	28
JS/S 100V1000W/S		100	1000	48	225	180	22000	3200	200	C-7A	24
JS/S 100V1000W/L		100	1000	48	300	225	22000	3200	200	C-7A	25
JS100V1500W B/E		100	1500	35	145	105	34500	3050	500	C-13	22
BWF 120V 2000W	BWF	100	2000	25	190.5	133.4	59000	3200	500	CC-8	26
BWG 120V 2000W	BWG	100	2000	25	190.5	133.4	57200	3200	500	CC-8	26

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)