

HOT JET S 230 V

SPECIFICATIONS

Attribute	Unit	Value
Voltage	V~	230
Power consumption	W	460
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Air flow (20°C)	l/min	20 – 80
Pressure static	Pa	max. 1600 (16 mbar)
Noise emission level LpA dB		59
Size (L x ø)	mm	235 x 70, handle Ø 40
Weight	kg	0.6 (with 3 m cord)
Marking of conformity		CE
Approval mark		Ⓢ
Certification scheme		CCA
Protection class II		□



勝特力材料 886-3-5753170
勝特力電子 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

ACCESSORIES



Tubular nozzle ø 5 mm push-fit on HOT JET S, LE MINI, LE MINI SENSOR

107.144: Tubular nozzle Ø 5 mm, push-fit



Wide slot nozzle 20 mm push-fit on HOT JET S

107.142: Wide slot nozzle 20 mm, push-fit



Sieve reflector 35 x 20 mm push-fit on HOT JET S

107.310: Sieve reflector 35 x 20 mm, push-fit



Spoon reflector 25 x 30 mm push-fit on HOT JET S

107.312: Spoon reflector 25 x 30 mm, push-fit



Sieve reflector 50 x 35 mm push-fit on HOT JET S

107.311: Sieve reflector 50 x 35 mm, push-fit



Pressure roller 28 mm (PTFE)

106.976: Pressure roller 28 mm (PTFE)

Pressure roller 28 mm (silicon)



106.977: Pressure roller 28 mm (silicon)

One-arm pressure roller 40 mm, with ball bearings (silicon)



106.975: One-arm pressure roller 40 mm, with ball bearings (silicon)

Customs seal roller



106.981: Customs seal roller


勝特力材料 886-3-5753170
勝特力電子 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Pressure roller with ball bearings (brass)



106.972: Pressure roller with ball bearings (brass)

Tacking nozzle push-fit on tubular nozzle Ø 5 mm



106.996: Tacking nozzle, push-fit on tubular nozzle Ø 5mm

Speed welding nozzle 4.5 x 12mm for fillet seams



107.139: Speed welding nozzle 4.5 x 12mm for fillet seams, push-fit on tubular nozzle Ø 5mm

Speed welding nozzle for tape 8 mm push-fit on tubular nozzle Ø 5mm



107.137: Speed welding nozzle for tape 8 mm, push-fit on tubular nozzle Ø 5mm

Speed welding nozzle with small air-slide, push-fit on Tubular nozzle Ø 5mm



105.431: Speed welding nozzle 3 mm, small air-slide, push-fit on tubular nozzle Ø 5 mm
105.432: Speed welding nozzle 4 mm, small air-slide, push-fit on tubular nozzle Ø 5mm
105.433: Speed welding nozzle 5 mm, small air-slide, push-fit on Tubular nozzle Ø 5 mm

Speed welding nozzle 3, 4, 5 mm push-fit on tubular nozzle Ø 5 mm




106.989: Speed welding nozzle 3 mm, push-fit on tubular nozzle Ø 5 mm
106.990: Speed welding nozzle 4 mm push-fit, on tubular nozzle Ø 5 mm
106.991: Speed welding nozzle 5 mm, push-fit on tubular nozzle Ø 5 mm

Speed welding nozzle 5.7, 7 mm push-fit on tubular nozzle Ø 5 mm



106.992: Speed welding nozzle 5.7 mm, push-fit on tubular nozzle Ø 5 mm
106.993: Speed welding nozzle 7 mm, push-fit on tubular nozzle Ø 5 mm

Sieve reflector 12 x 10 mm push-fit on tubular nozzle Ø 5mm



107.324: Sieve reflector 12 x 10 mm, push-fit on tubular nozzle Ø 5mm