


IE5270

IEB21,5-AROG/PH
Metal thread M8x1
Cable


Sensing range 1,5mm [f]
flush mountable

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw



Electrical design	DC PNP/NPN
Output	normally open
Operating voltage [V]	5...36 DC
Current rating [mA]	200
Minimum load current [mA]	4
Voltage drop [V]	< 4,6
Leakage current [mA]	< 0,8
Real sensing range [mm]	1,5 ± 10%
Operating distance [mm]	0...1,2
Switch-point drift [% / Sr]	-10...+10
Hysteresis [% / Sr]	3...15
Switching frequency [Hz]	1000
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Operating temperature [°C]	0...+60
Protection	IP 67, III
EMC	EN 60947-5-2; EN 55011 class B
Housing material	brass nickel-plated Pocan
Function display Switching status LED	yellow
Connection Wiring	PUR cable highly flexible / 2m; 2 x 0,14mm ²

Core colours
BN brown
BU blue



Accessories (included)

2 lock nuts