

LEADMAN Switching Power Adapter

LP-1250 12V/5A



Features :

- High Efficiency, high reliability
- Universal full range AC input
- Over voltage protection
- Short circuit protection
- Low ripple noise
- 1 year warranty

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Input specification :

- Voltage Range : 100~240VAC
- Frequency : 47~63Hz
- Current : 0.49A Max
- Inrush current : 42A Max/100 Vac;84A Max/240 Vac (Cold stabt at 25℃ full load)
- Leakage current : <5mA@1500V

Output specification :

- Single Voltage : +12V
- MAX. Load : 5A
- MIN. Load : 0.1A
- Regulation : 11.40V Min12.00V Typ.12.60VMax
- Ripple & Noise : 120mV Max
- Efficiency : 80% Typical(At norminal line voltage full load)
- Total Power : 60W Max

Environment :

- Operating temperature range : 0 °C ~+40 °C
- Storage temperature : -40 °C ~+70 °C
- Operating humidity : 10% to 90% RH(Non-Condensing)
- Storage humidity : 5% to 95% RH(Non-Condensing)

Reliability :

- MTBF : >50,000 hours
- Burn in test : 4 hours, 45 +/- 5 °C , full load, 220VAC 50Hz