

Model

MCO-1510A

MCO-1510B

Package	14Pin Dip(Half Size)		14Pin Dip(Half Size)	
Frequency Range (Fo)	1.000MHz to 100.000MHz		1.000MHz to 70.000MHz	
Frequency Stability (f/fo)	A=±25ppm,B=±50ppm,C=±100ppm			
Operating Temperature Range (TOPR)	0°C to 70°C,-40°C to 85°C(Available)			
Storage Temp. Range (Tstg)	-55°C to 125°C			
Power Supply Voltage (Vdd)	5Vdc±0.5Vdc		3.3Vdc±0.3Vdc	
Aging (at25°C)	±5ppm/year Max.			
	1.000MHz to 23.999MHz 20mA Max.		1.000MHz to 23.999MHz 10mA Max.	
	24.000MHz to 50.000MHz 30mA Max.		24.000MHz to 50.000MHz 20mA Max.	
	50.000MHz to 70.000MHz 40mA Max.		50.000MHz to 70.000MHz 30mA Max.	
	70.000MHz to 100.000MHz 60mA Max.		40 to 60%Normal,45 to 55%Tight	
Output Symmetry(At50% Vdd)	±5ns Max.			
Rise and Fall Time(Tr,Tf) 10% to 90% of Waveform W/Hcmos Load				
Output Voltage Logic High (Voh)	4.5V min		2.7Vdc minimum	
Output Voltage Logic Low (Vol)	0.5Vdc max		0.4Vdc max	
Output Load	1.000MHz to 40.000MHz	10TTL Load or 50pF HCMOS Load	1.000MHz to 24.000MHz	2TTL Load or 15pF HCMOS Load Max
	40.000MHz to 1000.000MHz	10TTL Load or 15pF HCMOS Load	24.000MHz to 70.000MHz	15pF HCMOS Load Max
pin 1			No Connection	No Connection to Enables Output
Tri-State Tri-			Vih	2.2V dc Minimum to Enable Output
Input Voltage			Vil	0.8Vdc Max.to disable Out@ut

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Mechanical Dimensions

