



Part No.	型号	MKA-10110
Total Length	总长度	41.8 mm
Glass Length	玻璃长度	10 mm
Glass Diameter	直径	1.8 mm
Contact Form	触点形式	1A (SPST-NO)
Contact Position	触点位置	SYM
Contact Material	触点材质	Ru
Contact Rating	触点负载	10W
Max. Switching Voltage	最大开关电压	100 VDC / VAC
Max. Switching Current	最大开关电流	0.5A
Contact Resistance (at initial value)	接触电阻 (初始值)	100 mOhms
Pull In Value (AT)	启动值	10-35
Drop Out Value (AT)	释放值	4
Operation Time	动作时间	0.5 mSec.(Max.)
Release Time	释放时间	0.3 mSec.(Max.)
Breakdown Voltage	耐高压	150 VDC
Contact Capacitance	触点电容	0.5 pF
Insulation Resistance	绝缘电阻	10 ⁹ Ohms
Resonant Frequency	谐振频率	5 kHz
Operation Temperature	工作温度范围	-60 °C ~+125 °C
High Humidity	最高湿度	98% (Max.)
Operation Frequency	最高工作频率	400 Hz
Electrical Life	电气寿命	5×10 ⁶ (50mV, 5 μA) 5×10 ⁶ (5V, 10mA) 1×10 ⁵ (24V, 250mA)
Test Coil	测试线圈	5000 580 Ohm
Leads	引线脚	Gold-Plated 镀金
Safety	安全认证	UL