

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## 免洗錫絲 No./Clean SMT Solder Wire

固品為因應現代生態環境保護，特以最先進之生產技術製造非鹵素免洗錫絲，使其在銲接及修補上迅速達成清潔之效果。

In responding to a global call for environmentalism, KU PING has applied the most advanced technology to produce unwashable solder wire which allows fast cleaning while it is used for welding and repairing.

### 特點 Features

- 具備雙相機型，任何型態銲接均能迅速完成。
- 非鹵素，不腐蝕，不飛濺，不起臭味。
- 殘留物少，銲點光澤，乾淨。
- Two-phase model allows easy welding and repairing.
- No halogens, no splash, uncorrodible, and without odour.
- Less residue, shinny and clean solder spot.

### 品種 Classification

| 項目<br>Item | 助錫劑含量<br>(Wt%)<br>Content<br>of flux | 乾燥度<br>Dryness | 氯含量<br>(Wt%)<br>Content<br>of<br>Chlorine | 銅板腐蝕<br>Corrosion<br>on<br>Copper<br>Plate | 水溶性<br>抵抗<br>(Ω cm)<br>Aqueous<br>solution<br>resistant | 絕緣抵抗<br>(Ω)<br>Insulation<br>resistant | 助錫劑<br>軟化點<br>Flux<br>melting<br>point | 擴散率<br>(%)<br>Expansion | 特質<br>Features |
|------------|--------------------------------------|----------------|---|--|---|--|--|-------------------------|----------------|
| K<br>TPYE  | 2%-2.5%                              | PASS           | 0%  | PASS                                       | OVER<br>100K  | 1 X 10 <sup>2</sup><br>OVER            | 95°C                                   | 85%<br>OVER             | 銲接用            |
| TYPE       | 1.1%-1.4%                            | PASS           | 0%  | PASS                                       | OVER<br>100K  | 1 X 10 <sup>2</sup><br>OVER            | 95°C                                   | 75%<br>OVER             | 修補用            |