



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

TITLE : NON HEAT-SHRINKABLE TUBING

MATERIAL : P.V.C  
 COLOR : BLACK/CLEAR  
 UNIT : mm



PART NO.	L=FEET(M)/ROLL
P0.864~P5.94	1000(304.8)
P6.68~P11.1B	500(152.4)
P12.7B	500(152.4)
P11.1	250(76.2)
P12.7	250(76.2)

PART NO.	SIZE AWG	INSIDE DIAMETER	CAT.No. DEV-300 (300V,105°C)			CAT.No. DEV-600 (600V,105°C)		
			MIN THICKNESS AT TNY POINT	AVG THICKNESS	OUTSIDE DIAMETER	MIN THICKNESS AT TNY POINT	AVG THICKNESS	OUTSIDE DIAMETER
P0.864	20	0.864	0.330	0.40	1.70	0.431	0.60	2.10
P0.965	19	0.965	0.330	0.40	1.80	0.431	0.60	2.20
P1.067	18	1.067	0.330	0.40	1.90	0.431	0.60	2.30
P1.19	17	1.19	0.330	0.40	2.00	0.559	0.70	2.60
P1.34	16	1.34	0.330	0.40	2.15	0.559	0.70	2.75
P1.50	15	1.50	0.330	0.40	2.30	0.559	0.70	2.90
P1.68	14	1.68	0.330	0.40	2.50	0.559	0.70	3.10
P1.93	13	1.93	0.330	0.40	2.70	0.559	0.70	3.35
P2.16	12	2.16	0.330	0.40	3.00	0.559	0.70	3.60
P2.41	11	2.41	0.330	0.40	3.20	0.559	0.70	3.80
P2.69	10	2.69	0.330	0.40	3.50	0.559	0.70	4.10
P3.00	9	3.00	0.431	0.55	4.10	0.559	0.70	4.40
P3.38	8	3.38	0.431	0.55	4.50	0.559	0.70	4.80
P3.76	7	3.76	0.431	0.55	4.90	0.559	0.70	5.20
P4.22	6	4.22	0.431	0.55	5.35	0.559	0.70	5.65
P4.72	5	4.72	0.431	0.55	5.85	0.559	0.70	6.15
P5.28	4	5.28	0.431	0.55	6.40	0.559	0.70	6.70
P5.94	3	5.94	0.431	0.55	7.05	0.559	0.70	7.35
P6.68	2	6.68	0.431	0.55	7.80	0.559	0.70	8.10
P7.47	1	7.47	0.431	0.55	8.60	0.559	0.70	8.90
P8.38	0	8.38	0.431	0.55	9.50	0.559	0.70	9.80
P7.92	5/16"	7.92				0.559	0.70	9.35
P9.53	3/8"	9.53				0.559	0.70	10.95
P11.1	7/16"	11.10				0.559	0.70	12.50
P12.7	1/2"	12.70				0.559	0.70	14.10