

All The Products Produced By KUON YI Can Be Made,Designed And Modified To Their Customer's Requirements.
A Front Metal Shielding Piece Can Be Added If Required.




Electrical Specification:

- * Contact resistance: 30m ohm max. At ac 100mA max. 1KHz
- * Insulation resistance: 100M ohm min. At 500V DC
- * Durability(life test): 4000 cycles
- * Dielectric withstanding voltage: 500VAC at 60Hz for 1 minute
- * Insertion Force: 0.3~3.0Kg
- * Extraction Force: 0.3~3.0Kg

Material:

- * Housing: Thermoplastic
- * Barrel: Copper Alloy
- * Terminal Pin: Copper Alloy
- * Front Metal Shield: Copper Alloy
- * Spring Shield: Stainless




勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)




PCB LAYOUT
(BOTTOM VIEW)



RJ-1515-1






PCB LAYOUT
(BOTTOM VIEW)



RJ-1515-1A




勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



PCB LAYOUT
(BOTTOM VIEW)



RJ-1515-1AS



PCB LAYOUT
(BOTTOM VIEW)



RJ-1515-1B