

# S-P系列電磁接觸器

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

型名			S-P11			S-P12			S-P16		
馬達額定容量			KW	HP	A	KW	HP	A	KW	HP	A
CNS C4084	單相	100~110V	0.55	0.75	12	0.55	0.75	12	0.75	1	16
		200~220V	1.1	1.5	12	1.1	1.5	12	1.5	2	16
JIS C8325	三相	200~220V	3	4	12	3	4	12	3.7	5	16
JEM 1038		380~440V	4	5.5	9	4	5.5	9	5.5	7.5	12
AC3級 額定容量		500~550V	4	5.5	7	4	5.5	7	5.5	7.5	10
連續通電電流(Ith)			20			20			30		
AC1級電阻性負載額定容量(A)			20			20			30		
額定絕緣電壓(Ui) (V)			AC 600			AC 600			AC 600		
IEC 60947-4-1 EN 60947-4-1 DIN VDE 0660 AC3級 額定容量	三相	240V	3.5	4.5	13	3.5	4.5	13	4.5	6	18
		440V	5.5	7.5	12	5.5	7.5	12	7.5	10	16
		550V	5.5	7.5	9	5.5	7.5	9	7.5	10	13
		660V	5.5	7.5	7	5.5	7.5	7	7.5	10	9
連續通電電流(Ith)			20			20			30		
AC1級電阻性負載額定容量(A)			20			20			30		
額定絕緣電壓(Ui) (V)			AC 660			AC 660			AC 660		
UL 508 CSA-C22.2 額定容量	單相	110~120V		0.5	9.8		0.5	9.8		1	16
		220~240V		2	12		2	12		3	17
	三相	220~240V		3	9.6		3	9.6		5	15.2
		440~480V		7.5	11		7.5	11		10	14
		550~600V		10	11		10	11		10	11
連續通電電流(Ith) (A)			24			24			30		
額定絕緣電壓(Ui) (V)			AC 600			AC 600			AC 600		
NEMA等級			00			00			0		
補助接點	接點構成	標準	1a(1NO)			1a1b(1NO 1NC)			1a1b(1NO 1NC)		
		特殊	1b( 1NC )			2a( 2NC )					
	IEC 60947-5-1 EN 60947-5-1 額定電流(A) AC12級	110V	6			6			6		
		220V	5			5			5		
		440V	3			3			3		
		550V	3			3			3		
連續通電電流(Ith)(A)		16			16			16			
補助接點等級(UL)		A600			A600,P600			A600,P600			
電氣壽命(AC3級)(萬次)			100			100			100		
機械壽命(萬次)			500			500			500		
重量(Kg)			0.33			0.35			0.37		