



Product Description:

- Bare of tinned copper conductor.
- Color or number coded SR-PVC, PP, PE insulation.
- Cores cable under aluminum-mylar tape 100% Coverage.
- Bare stranded copper drain wire (22 AWG).
- Tinned copper braid shield 85% coverage.
- PVC jacketed instrumentation control cable.
- Rated temperature 60°C (nom), 75°C, 105°C available.
- Minimum insulation resistance: 50M Ω -km/20°C

說明:

- 裸銅線或鍍錫銅線絞合導體
- 顏色或號碼識別: SR-PVC, PP, PE 絕緣芯線
- 鋁箔麥拉 100%遮蔽
- 鍍錫銅線絞合地線 (22 AWG)
- 裸銅線銅網編織隔離
- PVC 外被, 溫度等級 60°C, 亦可指定 75°C, 105°C
- 最小絕緣電阻: 50M Ω -KM/20°C 以上

Conductor Size			No. of Core	Insu. Nom. OD	Jacket Nom. OD (mm) mm*mm	Standard Jacket Color No/mm	Conductor Size			No. of Core	Insu. Nom. OD	Jacket Nom. OD (mm)	Standard Jacket Color
mm*mm	No/mm	AWG					mm*mm	No/mm	AWG				
0.5	20/0.18	20	2	1.8	5.8	Black	1.25	50/0.18 (7/0.45)	16	2	2.5	7.4	Black
			3	1.8	6.5	Black				3	2.5	8.0	Black
			4	1.8	7.0	Black				4	2.5	8.8	Black
			5	1.8	7.5	Black				5	2.5	10.0	Black
			6	1.8	8.0	Black				6	2.5	11.0	Black
			7	1.8	8.0	Black				7	2.5	11.0	Black
			8	1.8	8.7	Black				8	2.5	11.8	Black
			10	1.8	10.0	Black				10	2.5	13.4	Black
			12	1.8	10.5	Black				12	2.5	13.8	Black
			16	1.8	11.8	Black				16	2.5	15.6	Black
			20	1.8	13.0	Black				20	2.5	16.7	Black
			24	1.8	14.5	Black				24	2.5	19.0	Black
30	1.8	15.0	Black	30	2.5	20.3	Black						
0.75	30/0.18	18	2	2.3	7.0	Black	2	37/0.26 (7/0.6)	14	2	3.0	8.8	Black
			3	2.3	7.5	Black				3	3.0	9.6	Black
			4	2.3	8.4	Black				4	3.0	10.4	Black
			5	2.3	9.2	Black				5	3.0	11.8	Black
			6	2.3	10.5	Black				6	3.0	12.6	Black
			7	2.3	10.5	Black				7	3.0	12.6	Black
			8	2.3	11.2	Black				8	3.0	13.5	Black
			10	2.3	12.6	Black				10	3.0	15.5	Black
			12	2.3	13.2	Black				12	3.0	16.0	Black
			16	2.3	14.5	Black				16	3.0	17.8	Black
			20	2.3	15.7	Black				20	3.0	19.6	Black
			24	2.3	17.5	Black				24	3.0	22.0	Black
30	2.3	18.5	Black	30	3.0	23.5	Black						

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)