

SF51G THRU SF57G

SUPER FAST GLASS PASSIVATED RECTIFIERS

FEATURES:

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- Good for switching mode application

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

MECHANICAL DATA

Case : Molded plastic


Epoxy: UL 94V-0 rate flame retardant

Lead : Axial leads, solderable per MIL-STD-202,
Method 208 guaranteed

Polarity : Color band denotes cathode end

Mounting Position : Any

Weight : 1.10 grams



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temp. unless otherwise specified.

Single phase, half sine wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20 %.


Characteristic	Symbol	SF 51G	SF 52G	SF 53G	SF 54G	SF 55G	SF 56G	SF 57G	Units
Maximum recurrent peak reverse voltage	V _{RRM}	50	100	150	200	300	400	600	Volts
Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	420	Volts
Maximum DC blocking voltage	V _{DC}	50	100	150	200	300	400	600	Volts
Maximum average forward rectified current .375"(9.5mm) lead length at Ta=55℃	I _(AV)	5.0							Amps
Peak forward surge current ,8.3ms single half sine-wave superimposed on rated load(JEDEC Method)	I _{FSM}	150							Amps
Maximum instantaneous forward voltage at 5.0 A	V _F	1.00				1.30		1.70	Volts
Maximum DC reverse current Ta=25℃ at rated DC blocking voltage Ta=125℃	I _R	5.0 100							μ A
Maximum reverse recovery time (note 1)	t _{rr}	35							nS
Typical junction capacitance(note 2)	C _j	50							pF
Operating and storage temperature range	T _j , T _{stg}	-65 to +150							℃

Notes : 1. Reverse recovery test condition : I_F=0.5A ; I_R=1.0A ; I_{RR}=0.25A

2. Measured 1MHz and applied reverse voltage of 4.0V DC

RATINGS AND CHARACTERISTIC CURVES SF51G THRU SF57G

FIG.1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)




FIG.3-TYPICAL FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.6-TYPICAL JUNCTION CAPACITANCE

