

Fuses and Fuse Systems

SILIZED 5SD, 5SE Semiconductor Fuses

Fuse links

Overview

SILIZED NEOZED fuse links



- Rated voltage U_n 400 V AC, 250 V DC
- Rated current I_n 10 ... 63 A
- Sizes D01 and D02
- Operational class gR

SILIZED DIAZED fuse links



- Rated voltage U_n 500 V AC, 500 V DC
- Rated current I_n 16 ... 100 A
- Operational class gR
- Characteristic super quick

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Selection and ordering data

Size	I_n	Order No.	Price 1 unit	PG	Weight 1 unit approx. kg	PS*/ P. unit Unit(s)
	A					

Rated voltage 400 V AC/250 V DC, operational class gR

Consumer packing, package of 10



D01	10	5SE1 310		016	0.006	10 units
	16	5SE1 316		016	0.007	10 units



D02	20	5SE1 320		016	0.012	10 units
	25	5SE1 325		016	0.012	10 units
	35	5SE1 335		016	0.012	10 units
	50	5SE1 350		016	0.013	10 units
	63	5SE1 363		016	0.014	10 units

Size	I_n	Identification color	Thread	Order No.	Price 1 unit	PG	Weight 1 unit approx. kg	PS*/ P. unit Unit(s)
	A							

Rated voltage 500 V AC/500 V DC

DIN VDE 0636-301

For semiconductor protection, designation, yellow ring
 operational class gR, characteristic super quick.
 For 30 A fuse links the DIAZED screw adapter DII for 25 A is used



DII	16	Gray	E27	5SD4 20		016	0.028	5 units
	20	Blue		5SD4 30		016	0.029	5 units
	25	Yellow		5SD4 40		016	0.031	5 units
	30			5SD4 80		016	0.031	5 units
DIII	35	Black	E33	5SD4 50		016	0.050	5 units
	50	White		5SD4 60		016	0.051	5 units
	63	Copper		5SD4 70		016	0.054	5 units
DIV	80	Silver	R1¼"	5SD5 10		016	0.110	3 units
	100	Red		5SD5 20		016	0.110	3 units