

CMP BATTERIES STANDBY DIVISION



Fax Transmission

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

To: From: Mike Carrington.

Company: Farnell Pages: 2

Fax: 0113 279 4279 Date: 28 January 1999

Re: Lithium Transport LTN-065-18-a CC:

European and world-wide carrier organisations classify lithium batteries in two categories, non-restricted and restricted. Lithium batteries falling into the non-restricted category can be shipped via any carrier without special requirements.

Lithium batteries are non-restricted if they meet the following requirements.

- Each cell contains no more than 0.5 g of lithium or lithium alloy.
- Each battery pack contains an aggregate quantity of no more than 1 g of lithium or lithium alloy
- Each cell is hermetically sealed
- Batteries are separated from each other in the pack so as to prevent shorting
- Batteries are packed in strong outside packaging (except when installed in electronic devices).

Table 1 indicates the Sonnenschein Lithium Battery models that belong to this category. Lithium Batteries that belong to the restricted category require special care during transportation. The requirements are shown Table 2.

Size	Non-Restricted Types				Restricted Types
Flat cells					
BEL	SL-340				
1/6D	SL-386				
1/10D	SL-389				
Small Cells					
½ AA	SL-350	SL-550	SL-750	SL2350	
2/3 AA	SL-361	SL-561	SL-761	SL2361	
AA	SL-360	SL-560	SL-760	SL2360	
Big Cells					
C					SL-770 SL2770
D					SL780 SL2780
DD					SL-790
Computer Batteries					
Computer-Battery	SL-360/461				
Computer-Battery	SL-360/486				

Table 1

Correlation between Sonnenschein Lithium Batteries, and transport categories.

The information contained within this facsimile is for use by the intended recipient only. Should this be inadvertently sent to the wrong place please return it to the number shown at the top of the first page.

Class	Limitations and Instructions	Passenger aircraft IATA DGR	Cargo aircraft IATA DGR	Road/Railway transport ADR/RID	Sea Transport IMDG Code
Lithium Batteries UN No. 3090, Class 9	Maximum amount of lithium per cell Maximum amount of lithium per battery pack Maximum amount of lithium per inner packaging Maximum gross weight per package Packing group Packing Instruction Marking	Forbidden	12 g 500 g 500 g 35 kg II 903 Hazard Label Handling Label for cargo only	12 g 500 g 500g 100 kg II Hazard Label	12 g 500 g 500g 250 kg II
Lithium Batteries contained in equipment UN No. 3091, Class 9	Maximum amount of lithium per cell Maximum amount of lithium per battery pack Maximum amount of lithium per any piece of equipment Maximum gross weight per package Packing group Packing Instruction Marking	3 g 125 g 5 kg II 912 Hazard Label	12 g 500 g 5 kg II 912 Hazard Label	12 g 500 g 100 kg II Hazard Label	12 g 500 g max. 10 batts 250 kg II

Table 2.

Transport regulations for lithium batteries falling into the restricted category as per table 1:

Cells containing more than 0.5 g of lithium and battery packs containing more than 1 g of Lithium.

Packaging instruction and lithium contents are available from Sonnenschein Lithium upon request.

The applicable documents are:

ADR: European Agreement concerning the international Carriage of Dangerous Good. by Road
 IATA DGR: International Air Transport Association, Dangerous Goods Regulations, 38th Edition, 1 January 1995.

IMDG Code: International Maritime Dangerous Goods Code

RID: International Statutory Order on the Conveyance of Dangerous Goods by Rail

UN: United Nations Recommendations on the Transport of Dangerous Goods, Tests and Criteria.

Mgc/lithium/065-18-a