

太陽能電池規格一覽表(室 外)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

型號		尺寸 , 毫米			電 性		環境條件	備 註
Type	Model	寬	長	厚度	Vop, V	Iop, mA		
SC	5030	50.00	29.00	2.00	1.8	26.0	C	
SC	5848	57.80	48.20	2.00	8.0	8.0	C	
SC	7035	70.20	35.00	2.00	4.0	18.0	C	
SC	9728	96.80	28.00	2.00	6.0	15.0	C	
SC	12439	124.50	39.30	2.00	15.0	12.0	C	
SC	14633	145.70	32.50	2.00	9.6	13.0	C	
SP	0611	110.00	60.00	2.35	2.5	88.0	C	
SC	60110Z							
SP	0907	89.70	69.70	2.35	4.0	50.0	C	
SC	9070Z							
SP	1510	145.00	95.0	2.00	7.5	60.0	C	
SC	14595Z							
SP	1515	152.40	152.40	2.35	7.5	120.0	C	
SC	152152							
SP	1530	152.40	290.00	2.35	7.5	200.0	C	
SP	3007	295.00	74.00	2.35	14.5	55.0	C	
SC	29574Z							
SP	3030	304.80	304.80	2.35	17.0	177.0	C	
SC	305305Z							
SM	5120	30.00	60.00	5.20	0.5	280.0	C	
SM	5626	30.00	57.00	5.20	3.0	60.0	C	
SM	8626	29.00	84.00	5.20	3.0	95.0	C	
SM	1143	108.00	43.00	3.00	9.0	30.0	C	
SM	9063	92.00	63.00	3.00	9.0	50.0	C	
SM	5151	60.00	65.00	5.20	4.0	75.0	C	
SM	5055	60.00	65.00	5.20	2.5	150.0	C	
SM	1212	110.00	115.00	3.60	0.5	3200	C	Power Module
SM	3015	118.00	176.00	8.00	14.5	120.0	C	Power Module
SM	1530	118.00	176.00	8.00	7.5	200.0	C	Power Module
SM	1611	118.00	176.00	8.00	3.0	800.0	C	Power Module
SM	3544	365.00	450.00	35.00	14.5	1000	C	Power Module

備註 (1) a : FI 200 Luxs , 25°C b : FL 300 Luxs , 25°C c : AM1(100mW/cm) , 25°C

(2) 其它尺寸可依客戶需求作特殊設計

(3) SC、SP 係非晶系列，SM 係單晶系列