



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

- ZINC DIE-CASTING HOUSING, NICKLE-PLATED.
- ALL PORTS F FEMALE CONNECTOR, 75Ω.
- POWER PASSING 24VDC 0.5A MAX.
- BUILT-IN TWO GROUNDING BLOCK.
- TWO PIECES OF SCREWS ATTACHED.
- PARTICULARLY DESIGNED FOR EASY AND CONVENIENT INSTALLATION, EVEN THICKER 9mm CABLE.
- SCREENING FACTOR :
  - 5~470 MHz  $\geq$  75dB
  - 471~862 MHz  $\geq$  65dB
  - 950~2050MHz  $\geq$  55dB
  - 2050~2300MHz  $\geq$  45dB

ITEM MODEL	FREQUENCY (MHz)	INSERTION LOSS (dB)	ISOLATION (dB)	RETURN LOSS (dB)	DIMENSION (mm)	WEIGHT (g)
STV-1782B POWER PASS TO ONE PORT	5~47	4.5	11	11	54 X 58 X 26	100
	47~1000	4.7	20	12		
	1000~1750	5.3	17	11		
	1750~2050	5.8	16	10		
	2050~2300	6.8	13	10		