



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- ZINC DIE-CASTING HOUSING, NICKLE-PLATED.
- ALL PORTS F FEMALE CONNECTOR, 75Ω.
- POWER PASSING 24VDC 0.5A MAX.
- BUILT-IN TWO GROUNDING BLOCK.
- TWO PIECES OF SCREWS ATTACHED.
- PARTICULARLY DESIGNED FOR EASY AND CONVENEIENT INSTALLATION, EVEN THICKER 9mm CABLE.
- SCREENING FACTOR :
 - 5~470 MHz \geq 75dB
 - 471~862 MHz \geq 65dB
 - 950~2050MHz \geq 55dB
 - 2050~2300MHz \geq 45dB

ITEM MODEL	FREQUENCY (MHz)	INSERTION LOSS (dB)	ISOLATION (dB)	RETURN LOSS (dB)	DIMENSION (mm)	WEIGHT (g)
STV-1786B POWER PASS TO ONE PORT	5~47	12	20	6	120 X 58 X 26	186
	47~1000	12	20	10		
	1000~1750	14.5	18	8.0		
	1750~2050	16	16	10		
	2050~2300	17.5	13	7.0		