

MODEL TL-4920

International size reference: C, ER26500



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

TADIRAN LITHIUM BATTERIES

TECHNICAL DATA



(Typical values @+25°C for batteries stored for one year or less)

| | |
|--|-------------------|
| ■ Nominal capacity @ 3 mA, to 2 V | 8.5 Ah |
| ■ Rated voltage | 3.6 V |
| ■ Maximum recommended continuous current | 75 mA |
| ■ Maximum 1 sec. pulse capability | 200 mA |
| ■ Weight | 49.5 g (1.746 oz) |
| ■ Volume | 26 cc |
| ■ Operating temperature range | -55 °C to +85 °C |
| ■ U.L. Component Recognition, MH 12193 | |



AVAILABLE TERMINATIONS

| | |
|------------------------|---------------|
| SUFFIX- /S STANDARD | 15-4920-21000 |
| SUFFIX- /T SOLDER TABS | 15-4920-31000 |



XOL - Extended Operating Life

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance.

ECN 1501174 Rev. C 01/06