

TOSHIBA BIPOLAR DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TD62081AP, TD62081CP, TD62081F, TD62081AF, TD62082AP, TD62082CP
 TD62082F, TD62082AF, TD62083AP, TD62083CP, TD62083F, TD62083AF
 TD62084AP, TD62084CP, TD62084F, TD62084AF

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

8CH DARLINGTON SINK DRIVER


The TD62081AP/CP/F/AF Series are high-voltage, high-current darlington drivers comprised of eight NPN darlington pairs.

All units feature integral clamp diodes for switching inductive loads.

Applications include relay, hammer, lamp and display (LED) drivers.

FEATURES


- Output current (single output)
 500mA (Max.) (TD62081AP/F/AF series)
 400mA (Max.) (TD62081CP series)
- High sustaining voltage output
 35V (Min.) (TD62081F series)
 50V (Min.) (TD62081AP/AF series)
 100V (Min.) (TD62081CP series)
- Output clamp diodes
- Inputs compatible with various types of logic.
- Package type-AP, CP : DIP-18pin
- Package type-F, AF : SOP-18pin



Weight
 DIP18-P-300-2.54D : 1.478g (Typ.)
 SOP18-P-375-1.27 : 0.41g (Typ.)

TYPE	INPUT BASE RESISTOR	DESIGNATION
TD62081AP/CP/F/AF	External	General Purpose
TD62082AP/CP/F/AF	10.5-kΩ + 7V Zener diode	14~25V PMOS
TD62083AP/CP/F/AF	2.7kΩ	TTL, 5V CMOS
TD62084AP/CP/F/AF	10.5kΩ	6~15V PMOS, CMOS

PIN CONNECTION (TOP VIEW)




961001EBA2


- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

SCHEMATICS (EACH DRIVER)


TD62081AP / CP / F / AF




TD62082AP / CP / F / AF



TD62083AP / CP / F / AF



TD62084AP / CP / F / AF



(Note) The input and output parasitic diodes cannot be used as clamp diodes.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Output Sustaining Voltage	AP, AF	- 0.5~50	V
	CP	- 0.5~100	
	F	- 0.5~35	
Output Current	I _{OUT}	500	mA / ch
		400	
Input Voltage	V _{IN} (Note 1)	- 0.5~30	V
Input Current	I _{IN} (Note 2)	25	mA
Clamp Diode Reverse Voltage	AP, AF	50	V
	CP	100	
	F	35	
Clamp Diode Forward Current	I _F	500	mA
		400	
Power Dissipation	AP, CP	1.47	W
	F, AF	0.96	
Operating Temperature	T _{opr}	- 40~85	°C
Storage Temperature	T _{stg}	- 55~150	°C

(Note 1) Except TD62081AP/CP/F/AF

(Note 2) Only TD62081AP/CP/F/AF

RECOMMENDED OPERATING CONDITIONS (Ta = -40~85°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Sustaining Voltage	AP, AF	V _{CE (SUS)}		0	—	50	V
	CP			0	—	100	
	F			0	—	35	
Output Current	AP, CP	I _{OUT}	T _{pw} = 25ms, Duty = 10%, 8 Circuits	0	—	347	mA / ch
			T _{pw} = 25ms, Duty = 50%, 8 Circuits	0	—	123	
	F, AF		T _{pw} = 25ms, Duty = 10%, 8 Circuits	0	—	268	
			T _{pw} = 25ms, Duty = 50%, 8 Circuits	0	—	90	
Input Voltage	Except TD62081AP / CP / F / AF	V _{IN}		0	—	30	V
Input Voltage (Output On)	TD62082AP / CP / F / AF	V _{IN (ON)}		14	—	30	V
	TD62083AP / CP / F / AF			3.5	—	30	
	TD62084AP / CP / F / AF			8	—	30	
Input Current	Only TD62081AP / CP / F / AF	I _{IN}		0	—	5	mA
Clamp Diode Reverse Voltage	AP, AF	V _R		—	—	50	V
	CP			—	—	100	
	F			—	—	35	
Clamp Diode Forward Current	CP	I _F		—	—	400	mA
				—	—	320	
Power Dissipation	AP, CP	P _D		—	—	0.52	W
	F, AF			—	—	0.4	

ELECTRICAL CHARACTERISTICS (Ta = 25°C)


CHARACTERISTIC		SYMBOL	TEST CIR-CUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT		
Output Leakage Current	AP, AF CP F	ICEX	1	VCE = 50V	Ta = 25°C	—	—	50		
				VCE = 100V						
				VCE = 35V						
	AP, AF CP F			TD62082	F	VCE = 50V	Ta = 85°C	—	—	100
						VCE = 100V				
						VCE = 35V				
	AP, AF CP F			TD62084	F	VCE = 50V	VIN = 6V	—	—	500
						VCE = 100V				
						VCE = 35V				
	AP, AF CP F			TD62084	F	VCE = 50V	VIN = 1V	—	—	500
						VCE = 100V				
						VCE = 35V				
Collector-Emitter Saturation Voltage		VCE (sat)	2	IOUT = 350mA, IIN = 500μA	—	1.3	1.6	V		
				IOUT = 200mA, IIN = 350μA	—	1.1	1.3			
				IOUT = 100mA, IIN = 250μA	—	0.9	1.1			
Input Current	TD62082AP / CP / F / AF	IIN (ON)	2	VIN = 17V	—	0.82	1.25	mA		
				VIN = 3.85V	—	0.93	1.35			
	TD62084AP / CP / F / AF			VIN = 5V	—	0.35	0.5			
				VIN = 12V	—	1.0	1.45			
				IIN (OFF)	4	IOUT = 500μA, Ta = 85°C	50		65	—
Input Voltage (Output On)	TD62082AP / CP / F / AF	VIN (ON)	5	VCE = 2V, IOUT = 300mA	—	—	13	V		
				VCE = 2V, IOUT = 200mA	—	—	2.4			
	VCE = 2V, IOUT = 250mA			—	—	2.7				
	VCE = 2V, IOUT = 300mA			—	—	3.0				
	TD62084AP / CP / F / AF			VCE = 2V, IOUT = 125mA	—	—	5.0			
				VCE = 2V, IOUT = 200mA	—	—	6.0			
				VCE = 2V, IOUT = 275mA	—	—	7.0			
				VCE = 2V, IOUT = 350mA	—	—	8.0			
DC Current Transfer Ratio		hFE	2	VCE = 2V, IOUT = 350mA	1000	—	—			
Clamp Diode Reverse Current		IR	6	Ta = 25°C (Note)	—	—	50	μA		
				Ta = 85°C (Note)	—	—	100			
Clamp Diode Forward Voltage	CP	VF	7	IF = 350mA	—	—	2.0	V		
				IF = 280mA	—	—	1.8			
Input Capacitance		CIN	—		—	15	—	pF		

(Note) VR = VR MAX.


CHARACTERISTIC		SYMBOL	TEST CIRCUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Turn-On Delay	AP, AF	t_{ON}	8	$R_L = 125\Omega, V_{OUT} = 50V$	—	0.1	—	μs
	CP			$R_L = 312\Omega, V_{OUT} = 100V$	—	0.1	—	
	F			$R_L = 87.5\Omega, V_{OUT} = 35V$	—	0.1	—	
Turn-Off Delay	AP, AF	t_{OFF}		$R_L = 125\Omega, V_{OUT} = 50V$	—	0.2	—	
	CP			$R_L = 312\Omega, V_{OUT} = 100V$	—	3.0	—	
	F			$R_L = 87.5\Omega, V_{OUT} = 35V$	—	0.2	—	

TEST CIRCUIT


1. I_{CEX}




2. $V_{CE(sat)}, h_{FE}$




3. $I_{IN(ON)}$




4. $I_{IN(OFF)}$




5. $V_{IN(ON)}$





6. I_R



7. V_F



8. t_{ON} , t_{OFF}



- (Note 1) Pulse Width $50\mu s$, Duty Cycle 10%
 Output Impedance 50Ω , $t_r \leq 5ns$, $t_f \leq 10ns$
- (Note 2) See below.






INPUT CONDITION




TYPE NUMBER	R1	V_{IH}
TD62081AP/CP/F/AF	$2.7k\Omega$	3V
TD62082AP/CP/F/AF	0Ω	13V
TD62083AP/CP/F/AF	0Ω	3V
TD62084AP/CP/F/AF	0Ω	8V

- (Note 3) C_L includes probe and jig capacitance

PRECAUTIONS for USING

Utmost care is necessary in the design of the output line, COMMON and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.






勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

OUTLINE DRAWING
DIP18-P-300-2.54D

Unit : mm




Weight : 1.478g (Typ.)

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

OUTLINE DRAWING
 SOP18-P-375-1.27

Unit : mm



Weight : 0.41g (Typ.)