

ESD SAFE AND LOW COST DELTRIN SMALL PARTS TIPS

Vacuum Handling Tool Accessories

Small Parts Tips

These tips are designed for handling very tiny parts. Tips are available in ESD Safe Delrin plastic so there is no chance of static or mechanical damage. For a lower cost tip Non-ESD Safe Delrin is also available.

These tips must be used with continuous vacuum systems only.

- Beige Delrin - Static Dissipative temperature up to 212°F (100°C).
- White Delrin Acetal - Non ESD Safe temperatures up to 212°F (100°C).

Beige ESD Safe Delrin Small Parts Tips

VSPT1005-BD	Bent, 0.010" (0.25mm) OD x 0.005" (0.13mm) ID, Delrin
VSPT2010-BD	Bent, 0.020" (0.51mm) OD x 0.010" (0.25mm) ID, Delrin
VSPT2515-BD	Bent, 0.025" (0.64mm) OD x 0.015" (0.38mm) ID, Delrin
VSPT3020-BD	Bent, 0.030" (0.76mm) OD x 0.020" (0.51mm) ID, Delrin
VSPT4030-BD	Bent, 0.040" (1.02mm) OD x 0.030" (0.76mm) ID, Delrin
VSPT6040-BD	Bent, 0.060" (1.52mm) OD x 0.040" (1.02mm) ID, Delrin
VSPT7050-BD	Bent, 0.070" (1.78mm) OD x 0.050" (1.27mm) ID, Delrin
VSPT8060-BD	Bent, 0.080" (2.00mm) OD x 0.060" (1.52mm) ID, Delrin

VSPT1005-SD	Straight, 0.010" (0.25mm) OD x 0.005" (0.13mm) ID, Delrin
VSPT2010-SD	Straight, 0.020" (0.51mm) OD x 0.010" (0.25mm) ID, Delrin
VSPT2515-SD	Straight, 0.025" (0.64mm) OD x 0.015" (0.38mm) ID, Delrin
VSPT3020-SD	Straight, 0.030" (0.76mm) OD x 0.020" (0.51mm) ID, Delrin
VSPT4030-SD	Straight, 0.040" (1.02mm) OD x 0.030" (0.76mm) ID, Delrin
VSPT6040-SD	Straight, 0.060" (1.52mm) OD x 0.040" (1.02mm) ID, Delrin
VSPT7050-SD	Straight, 0.070" (1.78mm) OD x 0.050" (1.27mm) ID, Delrin
VSPT8060-SD	Straight, 0.080" (2.00mm) OD x 0.060" (1.52mm) ID, Delrin

White Non ESD Safe Delrin (Acetal) Small Parts Tips

VSPT1005-BA	Bent, 0.010" (0.25mm) OD x 0.005" (0.13mm) ID, Acetal
VSPT2010-BA	Bent, 0.020" (0.51mm) OD x 0.010" (0.25mm) ID, Acetal
VSPT2515-BA	Bent, 0.025" (0.64mm) OD x 0.015" (0.38mm) ID, Acetal
VSPT3020-BA	Bent, 0.030" (0.76mm) OD x 0.020" (0.51mm) ID, Acetal
VSPT4030-BA	Bent, 0.040" (1.02mm) OD x 0.030" (0.76mm) ID, Acetal
VSPT6040-BA	Bent, 0.060" (1.52mm) OD x 0.040" (1.02mm) ID, Acetal
VSPT7050-BA	Bent, 0.070" (1.78mm) OD x 0.050" (1.27mm) ID, Acetal
VSPT8060-BA	Bent, 0.080" (2.00mm) OD x 0.060" (1.52mm) ID, Acetal

VSPT1005-SA	Straight, 0.010" (0.25mm) OD x 0.005" (0.13mm) ID, Acetal
VSPT2010-SA	Straight, 0.020" (0.51mm) OD x 0.010" (0.25mm) ID, Acetal
VSPT2515-SA	Straight, 0.025" (0.64mm) OD x 0.015" (0.38mm) ID, Acetal
VSPT3020-SA	Straight, 0.030" (0.76mm) OD x 0.020" (0.51mm) ID, Acetal
VSPT4030-SA	Straight, 0.040" (1.02mm) OD x 0.030" (0.76mm) ID, Acetal
VSPT6040-SA	Straight, 0.060" (1.52mm) OD x 0.040" (1.02mm) ID, Acetal
VSPT7050-SA	Straight, 0.070" (1.78mm) OD x 0.050" (1.27mm) ID, Acetal
VSPT8060-SA	Straight, 0.080" (2.00mm) OD x 0.060" (1.52mm) ID, Acetal

Our machined small parts tips are designed to be used with a continuous vacuum source for handling parts as small as .006" (.152mm).

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Delrin
Tip
Stainless
Steel

Zinc
Luer
Fitting

Acetal
Tip
Stainless
Steel

Zinc
Luer
Fitting

