

WIMA MKS 2



Metallized Polyester (PET) Capacitors in PCM 5 mm

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

Special Features

- High volume/capacitance ratio
- Self-healing
- According to RoHS 2002/95/EC

Typical Applications

For general DC-applications e.g.

- By-pass
- Blocking
- Coupling and decoupling
- Timing

Construction


Dielectric:

Polyethylene-terephthalate (PET) film

Capacitor electrodes:

Vacuum-deposited

Internal construction:



Encapsulation:

Solvent-resistant, flame-retardent plastic case with epoxy resin seal, UL 94 V-0

Terminations:

Tinned wire.

Marking:

Colour: Red. Marking: Silver/White.
 Epoxy resin seal: Red

Electrical Data

Capacitance range:

1000 pF to 6.8 µF (E12-values on request)

Rated voltages:

16 VDC, 50 VDC, 63 VDC, 100 VDC,
 250 VDC, 400 VDC, 630 VDC

Capacitance tolerances:

±20%, ±10%, ±5%

Operating temperature range:

-55° C to +100° C

Climatic test category:

55/100/21 in accordance with IEC

Insulation resistance at +20° C:

U _r	U _{test}	C ≤ 0.33 µF	0.33 µF < C ≤ 6.8 µF
16 VDC	10V	≥ 3.75 x 10 ³ MΩ (mean value: 1 x 10 ⁴ MΩ)	≥ 1000 sec (MΩ x µF) (mean value: 3000 sec)
50 VDC	10V	≥ 5 x 10 ³ MΩ (mean value: 3 x 10 ⁴ MΩ)	≥ 1000 sec (MΩ x µF) (mean value: 3000 sec)
63 VDC	50V	≥ 1 x 10 ⁴ MΩ (mean value: 5 x 10 ⁴ MΩ)	≥ 1250 sec (MΩ x µF) (mean value: 3000 sec)
≥ 100 VDC	100V	≥ 1.5 x 10 ⁴ MΩ (mean value: 1 x 10 ⁵ MΩ)	≥ 3000 sec (MΩ x µF) (mean value: 6000 sec)

Test specifications:

In accordance with IEC 60384-2 and EN 130400

Test voltage: 1.6 U_r, 2 sec.

Voltage derating:

A voltage derating factor of 1.25 % per K must be applied from +85° C for DC voltages and from +75° C for AC voltages

Reliability:

Operational life > 300000 hours
 Failure rate < 2 fit (0.5 x U_r and 40° C)

Measuring time: 1 min.

Dissipation factors at + 20° C: tan δ

at f	C ≤ 0.1 µF	0.1 µF < C ≤ 1.0 µF	C > 1.0 µF
1 kHz	≤ 8 x 10 ⁻³	≤ 8 x 10 ⁻³	≤ 10 x 10 ⁻³
10 kHz	≤ 15 x 10 ⁻³	≤ 15 x 10 ⁻³	-
100 kHz	≤ 30 x 10 ⁻³	-	-

Maximum pulse rise time:

Capacitance pF/µF	Pulse rise time V/µsec max. operation/test							
	16VDC	50VDC	63VDC	100VDC	250VDC	400VDC	630VDC	
1000 ... 6800	-	-	-	-	-	-	110/1100	
0.01 ... 0.022	-	-	35/350	35/350	50/500	80/800	110/1100	
0.033 ... 0.068	-	-	20/200	25/250	50/500	80/800	90/900	
0.1 ... 0.47	-	10/100	15/150	20/200	50/500	80/800	-	
0.68 ... 1.0	-	8/80	12/120	15/150	25/250	-	-	
1.5 ... 3.3	-	8/80	7.5/75	10/100	-	-	-	
4.7	4/40	5/50	5/50	-	-	-	-	
6.8	3/30	3/30	3/30	-	-	-	-	

for pulses equal to the rated voltage

Mechanical Tests

Pull test on leads:

10 N in direction of leads according to IEC 60068-2-21

Vibration:

6 hours at 10...2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6

Low air density:

1kPa = 10 mbar in accordance with IEC 60068-2-13

Bump test:

4000 bumps at 390 m/sec² in accordance with IEC 60068-2-29

Packing

Available taped and reeled.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

WIMA MKS 2

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Continuation

General Data

Capacitance	16 VDC/10 VAC*				50 VDC/30 VAC*				63 VDC/40 VAC*				100 VDC/63 VAC*				250 VDC/160 VAC*				400 VDC/200 VAC*				630 VDC/220 VAC**															
	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**												
1000 pF																									3	7.5	7.2	5	3	7.5	7.2	5								
1500 "																									3	7.5	7.2	5	3	7.5	7.2	5								
2200 "																									3	7.5	7.2	5	3	7.5	7.2	5								
3300 "																									3	7.5	7.2	5	3	7.5	7.2	5								
4700 "																									3.5	8.5	7.2	5	3.5	8.5	7.2	5								
6800 "																									4.5	9.5	7.2	5	4.5	9.5	7.2	5								
0.01 μF									2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	5.5	11.5	7.2	5	5.5	11.5	7.2	5				
0.015 "									2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	7.2	13	7.2	5	7.2	13	7.2	5				
0.022 "									2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	3.5	8.5	7.2	5	3.5	8.5	7.2	5								
0.033 "									2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	3.5	8.5	7.2	5	4.5	9.5	7.2	5	4.5	9.5	7.2	5								
0.047 "									2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	3.5	8.5	7.2	5	4.5	9.5	7.2	5	8.5	14	7.2	5	8.5	14	7.2	5				
0.068 "									2.5	6.5	7.2	5	2.5	6.5	7.2	5	2.5	6.5	7.2	5	3.5	8.5	7.2	5	5.5	11.5	7.2	5	5.5	11.5	7.2	5								
0.1 μF									2.5	6.5	7.2	5	2.5	6.5	7.2	5	4.5	9.5	7.2	5	7.2	13	7.2	5	7.2	13	7.2	5												
0.15 "									2.5	6.5	7.2	5	3.5	8.5	7.2	5	5	10	7.2	5	5	10	7.2	5	8.5	14	7.2	5	8.5	14	7.2	5								
0.22 "									3	7.5	7.2	5	3.5	8.5	7.2	5	5.5	11.5	7.2	5	5.5	11.5	7.2	5	11	16	7.2	5	11	16	7.2	5								
0.33 "					2.5	6.5	7.2	5	3.5	8.5	7.2	5	4.5	9.5	7.2	5	7.2	13	7.2	5	7.2	13	7.2	5																
0.47 "					3	7.5	7.2	5	3.5	8.5	7.2	5	4.5	9.5	7.2	5	8.5	14	7.2	5	8.5	14	7.2	5																
0.68 "					3.5	8.5	7.2	5	4.5	9.5	7.2	5	5	10	7.2	5	11	16	7.2	5	11	16	7.2	5																
1.0 μF					3.5	8.5	7.2	5	5	10	7.2	5	7.2	13	7.2	5	7.2	13	7.2	5																				
1.5 "					4.5	9.5	7.2	5	5.5	11.5	7.2	5	8.5	14	7.2	5	8.5	14	7.2	5																				
2.2 "					5	10	7.2	5	7.2	13	7.2	5	11	16	7.2	5	11	16	7.2	5																				
3.3 "					5.5	11.5	7.2	5	7.2	13	7.2	5	7.2	13	7.2	5																								
4.7 "	5.5	11.5	7.2	5	7.2	13	7.2	5	8.5	14	7.2	5	8.5	14	7.2	5																								
6.8 "	7.2	13	7.2	5	8.5	14	7.2	5	11	16	7.2	5	11	16	7.2	5																								



* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{rms} + U_{DC} \leq U_r$

** PCM = Printed circuit module = lead spacing

Dims. in mm.

Taped version see page 104.







$d = 0.5 \phi$



Impedance change with frequency (general guide).

Rights reserved to amend design data without prior notification.

Permissible AC voltage in relation to frequency at 10° C internal temperature rise (general guide).





Recommendation for Processing and Application of Through-Hole Capacitors

Soldering Process


A preheating of through-hole WIMA capacitors is allowed for temperatures $T_{\max} < 100^{\circ}\text{C}$.
 In practice a preheating duration of $t < 5$ min. has been proven to be best.

Single wave soldering

Soldering bath temperature: $T < 260^{\circ}\text{C}$
 Immersion time: $t < 5$ sec

Double wave soldering

Soldering bath temperature: $T < 260^{\circ}\text{C}$
 Immersion time: $2 \times t < 3$ sec



WIMA Quality and Environmental Philosophy

ISO 9001:2000 Certification

ISO 9001:2000 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2000 of our factories by the VDE inspectorate certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application of WPCS during production process:

- incoming material inspection
- metallization
- film inspection
- schoopage
- pre-healing
- lead attachment
- cast resin preparation/encapsulation
- 100% final inspection
- AQL check

WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- Lead
- PCB
- CFC
- Hydrocarbon chloride
- Chromium 6+
- PBB/PBDE
- Arsenic
- Cadmium
- Mercury
- etc.

We merely use pure, recyclable materials for packing our components, such as:

- carton
- cardboard
- adhesive tape made of paper
- polystyrene

We almost completely refrain from using packing materials such as:

- foamed polystyrene (Styropor®)
- adhesive tapes made of plastic
- metal clips

RoHS Compliance

According to the RoHS Directive 2002/95/EC certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei konform RoHS 2002/95/EG

WIMA capacitors are lead free in accordance with RoHS 2002/95/EC

Tape for lead-free WIMA capacitors

DIN EN ISO 14001:2005

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2005. The certification has been granted in June 2006.



Typical Dimensions for Taping Configuration




Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5*mm

*PCM 27.5 tapping possible with two feed holes between components

Designation	Symbol	Dimensions for Radial Taping							
		PCM 2.5 tapping	PCM 5 tapping	PCM 7.5 tapping	PCM 10 tapping*	PCM 15 tapping*	PCM 22.5 tapping	PCM 27.5 tapping	
Carrier tape width	W	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	
Hold-down tape width	W ₀	6.0 for hot-sealing adhesive tape	6.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	
Hole position	W ₁	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	
Hold-down tape position	W ₂	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	
Feed hole diameter	D ₀	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	
Pitch of component	P	12.7 ±1.0	12.7 ±1.0	12.7 ±1.0	25.4 ±1.0	25.4 ±1.0	38.1 ±1.5	38.1 ±1.5 or 50.8 ±1.5	
Feed hole pitch	P ₀	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	
Feed hole centre to lead	P ₁	5.1 ±0.5	3.85 ±0.7	2.6 ±0.7	7.7 ±0.7	5.2 ±0.7	7.8 ±0.7	5.3 ±0.7	
Hole centre to component centre	P ₂	6.35 ±1.3	6.35 ±1.3	6.35 ±1.3	12.7 ±1.3	12.7 ±1.3	19.05 ±1.3	19.05 ±1.3	
Feed hole centre to bottom edge of the component	H _▲	16.5 ±0.3 18.5 ±0.5	16.5 ±0.3 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	
Feed hole centre to top edge of the component	H ₁	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 24.5 to 31.5	H+H _{component} < H ₁ 25.0 to 31.5	H+H _{component} < H ₁ 26.0 to 37.0	H+H _{component} < H ₁ 30.0 to 43.0	H+H _{component} < H ₁ 35.0 to 45.0	
Lead spacing at upper edge of carrier tape	F	2.5 ±0.5	5.0 ^{+0.8} _{-0.2}	7.5 ±0.8	10.0 ±0.8	15 ±0.8	22.5 ±0.8	27.5 ±0.8	
Lead diameter	d	0.4 ±0.05	0.5 ±0.05	0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05}	0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05}	0.8 ^{+0.08} _{-0.05}	0.8 ^{+0.08} _{-0.05}	0.8 ^{+0.08} _{-0.05}	
Component alignment	Δh	± 2.0 max.	± 2.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	
Total tape thickness	t	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	
Package (see also page 105)	▲	ROLL/AMMO			AMMO				
		REEL φ 360 max. φ 30 ±1	B 52 ±2 58 ±2 } depending on comp. dimensions		REEL φ 360 max. φ 30 ±1	B 52 ±2 58 ±2 or 66 ±2	REEL φ 500 max. φ 25 ±1	B 60 ±2 68 ±2 } depending on PCM and component dimensions	
Unit		see details page 107.							

▲ Please give „H“ dimensions and desired packaging type when ordering.

• Diameter of leads see General Data.

* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 1). P₀ = 12.7 or 15.0 is possible

Dim's in mm.

Please clarify customer-specific deviations with the manufacturer.