





勝特力材料 886-3-5753170
 勝特力電子(上海) 86-21-54151736
 勝特力電子(深圳) 86-755-83298787
 Http://www.100y.com.tw


XRJM-S-01-8-8-0-901

Shielded Packing Type
 1. SHIELD
 2. NO SHIELD
 3. SHIELD
 M-C Thru Hole V/LED 1 NO. OF PORTS
 NO. OF CONTACT
 SERIAL NUMBER
 LED COLOR OPTION



NOTES:

1. MATERIALS:
 HOUSING-NYLON ZYTEL FR-50
 HEAT DEFLECTION TEMP.255°
 BLACK COLOR, UL94V-0
 CONTACTS-0.35mm THICK PHOS-BRONZE PLATED
 WITH 150° HARD GOLD AND TIN/LEAD
 IN SOLDER AREA
 SHIELD-0.25mm THICK COPPER ALLOY,
 PLATED WITH TIN-LEAD OR NICKEL
2. CAVITY CONFORMS TO FCC RULES AND REGULATIONS
 PART 68,SUBPART F.
3. UNSPECIFIED TOLERANCE: .XX ±0.25(0.010)
 .X ±0.30(0.012)



PCB LAYOUT
 Ref.

CONNECTING THE INFORMATION			
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE RJ45 Connectors, 8P,8C, Shielded, Thru-Hole.			
PART NO. XRJM-S-01-8-8-0-901			
DIMENSIONS SHEET REV			
mmInch 1 1 of 1 01			
DATE 26/11/03			
CUSTOMER/NO.			
DWG NO. 001-2-8-8-0-901			
DRAWN JEFF			
CHKD FUTUEN			