



ZD905V
SOLDAPULLT® LONER

Hot Tip Desoldering and Soldering Station

- Independent controls for both soldering and desoldering tools
- High performance in a small footprint
- Requires clean and dry shop air, 60-90 psi
- External calibration helps with ISO9000 compliance
- Wide variety of nozzles and tips available

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



ZD505V
SOLDAPULLT®

Hot Tip Desoldering Station

- Requires clean and dry shop air, 60-90 psi
- Powerful 70W high output PTC element makes heavy duty multi-layer boards easy to desolder
- Adjustable hand tool provides comfortable working angles
- External calibration helps with ISO9000 compliance
- Burn resistant tool power cord and vacuum hose



ZD500DX
SOLDAPULLT® Self-Contained
Deluxe Hot Tip Desoldering Station



- Adjustable hand tool design provides comfortable working angles
- Powerful 70W high output PTC element makes heavy duty multi-layer boards easy to desolder
- External calibration helps with ISO9000 compliance
- Single burn-resistant tool power cord and vacuum hose


Specifications for Model ZD905V



Power Requirements
Power Rating
Heater Rating



Weight
Overall Dimension
Temperature Range
Temperature Regulation
Tip-to-Ground Voltage Leakage/Resistance



ZD905V-100	ZD905V-230	Options for ZD905V-230
100V, 50Hz 38W - 310W 24V, 70W	230V, 50Hz 38W - 310W 24V, 70W	ZD905V-230B British Standard Plug  ZD905V-230P No Plug 
2.7 kg		
140 mm x 229 mm x 241 mm		
205°C-427°C		
< 2mV/< 2 ohms		
±3°C		

Specifications for Model ZD505V



Power Requirements
Power Rating
Heater Rating

Weight
Overall Dimension
Temperature Range
Temperature Regulation
Tip-to-Ground Voltage Leakage/Resistance

ZD505V-100	ZD505V-230	Options for ZD505V-230
100V, 50Hz 20W - 150W 24V, 70W	230V, 50Hz 20W - 150W 24V, 70W	ZD505V-230B British Standard Plug  ZD505V-230P No Plug 
2.4 kg		
127 mm x 241 mm x 229 mm		
205°C-427°C		
< 2mV/< 2 ohms		
±3°C		



勝特力材料 86-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specifications for Model ZD500DX



Power Requirements
Power Rating
Heater Rating

Weight
Overall Dimension
Temperature Range
Temperature Regulation
Tip-to-Ground Voltage Leakage/Resistance

ZD500DX-100	ZD500DX-230	Options for ZD500DX-230
100V, 50Hz 95W - 200W 24V, 70W	230V, 50Hz 95W - 200W 24V, 70W	ZD500DX-230B British Standard Plug  ZD500DX-230P No Plug 
3.0 kg		
127 mm x 216 mm x 229 mm		
205°C-427°C		
< 2mV/< 2 ohms		
±3°C		