

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

ZTX-20 體視顯微鏡

ZTX-20 SERIES ZOOM STEREO MICROSCOPE



產品信息

型號：ZTX-20

規格：2X，4X 物鏡，WF20x 目鏡

技術性能：

1. 視場寬廣，成像清晰，立體感強
2. 45 傾斜雙目觀察，可 360 旋轉，鎖定目鏡，左目鏡同視度調節 $\pm 5\text{dp}$ ，出射筒距調節範圍為 55-75mm
3. 90 旋轉式物鏡，有三種可供選擇：1x/2x, 1x/3x, 2x/4x.
4. ZTX-20 為立柱式支架
5. 產品通過 CE 認證
6. 輸入電壓為 110V/60Hz 或者 220V/50Hz
7. 每台泡沫包裝，放入內紙箱，二台一個外箱
8. 多種附件可供選擇

選購附件：

1. 目鏡：WF5X，WF10X，WF15，WF20X
2. 附加物鏡 0.5X, 0.75X, 1.5X, 2X
3. 顯微攝像儀
4. 暗視場工作台
5. 珠寶夾
6. 黑白載物板（ 94.5mm ）
7. 磨砂玻璃載物板（ 94.5mm ）
8. 螢光燈 5W

9. 鹵素燈泡 12V10W

10. 環形燈 8W , 10W

11. 木箱

光源配置：

S1. 透射及反射照明均用鹵素燈 6V 12W

S2. 透射及反射照明均用鹵素燈 6V 12W , 可上下調光

S3. 透射照明用螢光燈 5W , 反射照明用鹵素 12V 10W

S4. 透射照明用螢光燈 5W , 反射照明用鹵素 12V 10W , 可調節亮度

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

光學參數：

目鏡	標準物鏡			附加物鏡							
	物鏡倍率	視場範圍	工作距離	0.5X		0.75X		1.5X		2.0X	
				視場範圍	工作距離	視場範圍	工作距離	視場範圍	工作距離	視場範圍	工作距離
5X	1X	20	80	37.5	120	24	75	14	40	11	25
	2X	10	80	19	120	12	75	7	40	5.5	25
	3X	7	80	12.5	120	8	75	4.5	40	3.5	25
	4X	5	80	19	120	6	75	3.5	40	2.8	25
10X	1X	20	80	37.5	120	25	75	14	40	11	25
	2X	10	80	19	120	12	75	7	40	5.5	25
	3X	7	80	12.5	120	8	75	4.5	40	3.5	25
	4X	5	80	19	120	6	75	3.5	40	3	25
15X	1X	15	80	30	120	18	75	10	40	8	25
	2X	7.5	80	15	120	9	75	5	40	4	25
	3X	5	80	9.5	120	6	75	3.5	40	3	25
	4X	3.8	80	7	120	4.5	75	2.8	40	2	25
20X	1X	10	80	19	120	12	75	7	40	5.5	25
	2X	5	80	10	120	6	75	3.5	40	2.5	25
	3X	3.5	80	6.2	120	4	75	2.4	40	2	25
	4X	2.5	80	4.7	120	3	75	2	40	1.5	25

Product Information

Type: ZTX-20

Specs: 2X, 4X Objective, WF10X EYEPIECES

Technical Performance:

1. Sharp stereo erect image over a wide field view
2. 45° inclined and 360° rotational binocular head with locked-ineyepiece. The left ocular-tube with diopter adjustment ± 5 dp, The interpupillary distance is between 55-75mm.
3. Three kinds of 90° rotational objective selection: 1x/2x, 1x/3x, 2x/4x.
4. ZTX-20 series supplied with pillar style stand.
5. Electric apparatus has CE approval
6. Power supply 110V/60Hz or 200V/50Hz
7. Each set packed in styrofoam and in an inner box. Three sets in one carton
8. A wide range of optional accessories.

Optional accessories:

1. Eyepiece WF5x, WF 10x, WF 15x, WF20x
2. Auxiliary objective 0.5x, 0.75x, 1.5x, 2x
3. Video Attachment ofr Microscope
4. Darkfield stage, 94.5mm
5. Jewel tweezer
6. White/black workingplate, 94.5mm
7. Frosted glass working plate, 94.5mm
8. Fluorescent bulb 5W
9. Halogen bulb 12V/10W
10. Ring fluorescent lighting 8W & 10W
11. Wooden cabinet with lock and key

Optical Parameters:

Eyepiece	Stand Objective			Auxiliary Objective							
	Objection	Field of View	Working Distance	0.5X		0.75X		1.5X		2.0X	
				Field of View	Working Distance	Field of View	Working Distance	Field of View	Working Distance	Field of View	Working Distance
5X	1X	20	80	37.5	120	24	75	14	40	11	25
	2X	10	80	19	120	12	75	7	40	5.5	25
	3X	7	80	12.5	120	8	75	4.5	40	3.5	25
	4X	5	80	19	120	6	75	3.5	40	2.8	25
10X	1X	20	80	37.5	120	25	75	14	40	11	25
	2X	10	80	19	120	12	75	7	40	5.5	25
	3X	7	80	12.5	120	8	75	4.5	40	3.5	25
	4X	5	80	19	120	6	75	3.5	40	3	25
15X	1X	15	80	30	120	18	75	10	40	8	25
	2X	7.5	80	15	120	9	75	5	40	4	25
	3X	5	80	9.5	120	6	75	3.5	40	3	25
	4X	3.8	80	7	120	4.5	75	2.8	40	2	25
20X	1X	10	80	19	120	12	75	7	40	5.5	25
	2X	5	80	10	120	6	75	3.5	40	2.5	25
	3X	3.5	80	6.2	120	4	75	2.4	40	2	25
	4X	2.5	80	4.7	120	3	75	2	40	1.5	25

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)